

# Eaton 8D0C13S03PA

Catalog Number: 8D0C13S03PA

Stainless Steel square flange receptacle, Nickel plating, with male short PCB contacts, keying A; 8D0C13S03PA

## General specifications



<b>Product Name</b>	<b>Catalog Number</b>
Eaton Souriau 8D PCB series MIL-DTL-38999 series III PC tail version connectors	8D0C13S03PA
<b>Product Height</b>	<b>Product Length/Depth</b>
28 mm	34.1 mm
<b>Product Weight</b>	<b>Product Width</b>
39 g	28 mm

Fitted with:

Shielding

Connector orientation

A

Connector type

Contact delivery

Loaded

Contact gender

Pin (Male)

Contact plating

Contact type

Coupling type

Degree of protection

IP67

Layout

03

Plating

Nickel

Shell material

Shell size

13

Mating cycles

500

Operating temperature - max

200 °C

Operating temperature - min

-65 °C

Receptacle type

Square Flange Receptacle

Number Of Contacts

3

Number of cavity #16

3

PCB diameter

0.5 mm

Salt spray

500 hour

Working voltage (Vrms)

1800 V



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)