Eaton 8D0L17M35SA

Catalog Number: 8D0L17M35SA

Composite square flange receptacle, Nickel plating, with female long PCB contacts, keying A; 8D0L17M35SA

General specifications

42 g

| Product Name | Catalog Number |
|--------------------------------------|----------------------|
| Eaton Souriau 8D PCB series MIL-DTL- | 8D0L17M35SA |
| 38999 series III PC tail version | Product Length/Depth |
| connectors | 35.26 mm |
| | 55.26 11111 |
| Product Height | Product Width |
| 33 mm | 33 mm |
| Product Weight | |





Product specifications

Fitted with:

Shielding

Connector orientation

А

Connector type

Contact delivery

Not delivered

Contact gender

Socket (Female)

Contact plating

Contact type

Coupling type

Degree of protection

IP67

Layout

35

Plating

Nickel

Shell material

Shell size

17

Mating cycles

500

Operating temperature - max 200 °C

200 0

Operating temperature - min -65 °C

Receptacle type

Square Flange Receptacle

Number Of Contacts

55

Number of cavity #22D

55

PCB diameter

0.5 mm

Resources

Salt spray

2000 hour

Working voltage (Vrms)

1300 V



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Righ Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia