Eaton DILM32-10(RDC60)

Catalog Number: DILM32-10(RDC60)

Eaton XT IEC mini contactor, 32A, 60 Vdc, 1NO, 32A, Frame C, 45 mm, 2, 5/ 10, 10, 20, 25 (1/3PH @120, 240/208, 240, 480, 600 V), Three-pole, Reversing, XT IEC series, Full voltage reversing miniature contactor, 400V, 15 kW

General specifications

Product Name Eaton XT IEC mini contactor

EAN 4015082772758

Product Height 3.5 in

Product Weight 1 lb

Certifications

UL Listed CSA Certified IEC 60947 EN 60947 Catalog Number DILM32-10(RDC60)

Product Length/Depth 2 in

Product Width 4 in

Compliances

RoHS Compliant CE Marked





Product specifications

Amperage Rating

32A

HP rating - max

2, 5/ 10, 10, 20, 25 (1/3PH @120,240/208,240,480,600 V)

Number Of Poles

Three-pole

Туре

Full voltage reversing miniature contactor

Voltage rating

400 V

Frame size

45 mm

Coil voltage

60 Vdc

Contact configuration

1 NO

Continuous ampere rating

32 A

Series

XT IEC

Operation

Reversing

Power consumption

15 kW

Resources

Multimedia

Contactors Explained

S1. E4. Ask the Experts - NEMA, IEC and DP contactors

Specifications and datasheets

Eaton Specification Sheet - DILM32-10(RDC60)

Powering Business Worldwide

Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia