

Eaton SMS9SE4K9

Catalog Number: SMS9SE4K9

Straight boardmount with short PCB male contacts (Gold & Tin plating); SMS9SE4K9

General specifications

Product Name	Catalog Number
Eaton Souriau SMS series quick mating plastic rectangular connector	SMS9SE4K9
	Product Length/Depth
	13.4 mm
Product Height	Product Width
16.2 mm	16 mm
Product Weight	
6.8 g	

Product specifications

Resources

Environmental conditions

Flammability rating UL94 V0

REACH

RoHS

Connector accessory option

No backshell possibility

Connector type

Receptacle

Contact delivery

Loaded

Contact gender

Pin (Male)

Contact plating

Gold

Contact type

PCB

Coupling type

Push-Pull

Degree of protection

IP30

Layout

9

Shell material

Plastic

Operating temperature - max

125 °C

Operating temperature - min

-55 °C

Receptacle type

Front Mount Panel

Number Of Contacts

9

Number of cavity #16

9



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)