



WIRE TABLE			
USB_A Plug CONTACT NO.	WIRE COLOUR	4 Pins Conn. CONTACT NO.	Ground Wire
1	RED	1	/
2	WHITE	2	/
3	GREEN	3	/
4	BLACK	4	/
	SHELL		BRAD

- Notes:
1. CABLE:2C 28AWG+2C 24 AWG USB CABLE OD=4.0±0.2MM
 2. ELECTRICAL TEST :CT:2.0 Ohm .IS:1.0M Ohm .DC 250V
 3. FLEXIBLE TEST:NO OPEN AND SHORT
ANGLE:±60° WEIGHT:500g
SPEED:30CPM TOTAL CYCLES:2000
 4. CABLE ASSY MUST BE 100% TESTED FOR OPEN,SHORT,MISWIRE.
 5. THE PRODUCT SHOULD BE FINISHED WITH THE CAP/COMPONENT No.14 COVERED
 6. DIMENSION MARKED ∇ SHOULD BE CHECKED BY Q.C. AND PROCESS ENGINEERS.
 7. PLEASE CONTACT FOXCNN SALES REPRESENTATIVE TO VERIFY PRODUCT DETAILS&AVAILABILITY

14	CORE OVERMOLD	A/R	TBD	PVC 65P,COLOR:BLACK
13	CAP	1	TBD	PE
12	CORE	A/R	020-0020-629	RH 4*5*2MM
11	SR OVERMOLD	A/R	TBD	PVC 40P,COLOR:BLACK
10	OVERMOLD	A/R	TBD	PVC 65P,COLOR:BLACK
9	INNER MOLD	A/R	901-0103-008	LOW PE
8	H.S. TUBE	A/R	080-S039-620	S901.BLACK ID=1.5mm
7	H.S. TUBE	A/R	080-2006-620	SUMITUBE:F32-4 BLACK ID=5.0
6	CORE	1	020-0021-629	RH 9.8*19*4.9
5	RAW CABLE	A/R	TBD	SHOW AS NOTES:1
4	TERMINAL	4	TBD	TBD
3	4 PIN CONN.	1	TBD	TBD
2	TOP SHELL	1	025-0302-455	MATERIAL:SPCC FINISH:CU:120U*MINI MOLD:100-200U
1	USB_A PLUG	1	UB2010C-07-4F	COLOR:BLACK(PBT),WITHOUT MARK
NO.		DESCRIPTION	Q'TY	REMARKS
X:±	X:±	UNITS	mm	
.X± 5	.X:±	MAT'L		
.XX±	.XX:±	FINISH		
.XXX±	.XXX:±	Q'TY		
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HON HAI PRECISION IND. CO., LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF HON HAI PRECISION IND. CO., LTD.				
NAME:(INTENDED USE)		CUSTOMER		
PART NO.(INTENDED USE)		CUBD005P-S62-EF		
APPD:		Y.M. Her 08/16/07		
CHKD:		Joe J.F.Chien 08/16/07		
DR:		Yongheng Chang 08/15/07		
TITLE:		USB A plug to 4pin conn.		
DWG NO.:		605-0000-2973		
SCALE	SHEET	REV.		
NONE	1/1	X2		