


WIRING DIAGRAM			
E1	DEFINITION	E2	E3
E1-P15			
E1-P14			
E1-P13			
E1-P12			
E1-P11			
E1-P10			
E1-P9			
E1-P8	RED +5V		E3-P2
E1-P7			
E1-P6			
E1-P5	BLACK GND		E3-P1
E1-P4			
E1-P3			
E1-P2			
E1-P1			
E1-S7	GND	E2-S7	
E1-S6	PCH_SATA_RX_P	E2-S6	
E1-S5	PCH_SATA_RX_N	E2-S5	
E1-S4	GND	E2-S4	
E1-S3	PCH_SATA_TX_N	E2-S3	
E1-S2	PCH_SATA_TX_P	E2-S2	
E1-S1	GND	E2-S1	



SECTION A-A

NOTES(注釋):

- HARMFUL MATERIAL CONTROL PLEASE FOLLOW DOC. NO. 'EPI12'.
本產品制程之原物料/零件必需符合EPI12環境物質管理規定。
- DIMENSION MARKED ∇ SHOULD BE CHECKED.
所有加注 ∇ 的尺寸必須檢驗。
- TEST SPEC: OPEN/SHORT TEST: 2K Ω hm
INSULATION RESISTANCE: 10M Ω hm/500VDC.
TEST TIME: 10ms
CONTACT RESISTANCE: 5 Ohm Max.
測試規格: 開路/短路 測試: 2K Ω hm.
絕緣電阻: 10M Ω hm/500VDC.
測試時間: 10ms.
導通電阻: 5 OHM MAX.

ITEM	PART NAME	DESCRIPTION
8	S-ATA CONN	SATA 7P CONN.,G/F
7	SATA CABLE	SATA CABLE,UL2725,30AWG,BLUE
6	CONTACT	CONTACT
5	HOUSING	PITCH 2.0MM,2PIN,WHITE
4	WIRE	UL1007,24AWG,RED
		UL1007,24AWG,BLACK
3	INNERMOLD	LD PE
2	OVERMOLD	PVC,BLACK
1	S-ATA CONN	SATA 22P CONN.,FEMALE,G/F

X.±	X°.±	UNITS mm	NAME<INTENDED USE>	FOXCONN® FOXCONN INTERCONNECT TECHNOLOGY LIMITED.
.X±	.X°±	MAT'L	MANUFACTURING	
.XX±	.XX°±	FINISH	PART NO.<INTENDED USE>	CLASS: <input type="checkbox"/> CONFIDENTIAL <input type="checkbox"/> SECRET <input checked="" type="checkbox"/> GENERAL
.XXX±	.XXX°±		FP22W07-0G-EF	APPD: Camvard 09/05'13
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF FOXCONN INTERCONNECT TECHNOLOGY LIMITED AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF FOXCONN INTERCONNECT TECHNOLOGY LIMITED.			CHKD: Paul Wu 09/05'13	DWG NO: 316-0000-5784
			DR: Shuo Liu 09/05'13	SCALE SHEET REV. N/A 1/1 A