



 PRODUCT-DETAILS

AF40N2-30-11-12

AF40N2-30-11-12 48-130V50/60HZ-DC Contactor



General Information

Extended Product Type	AF40N2-30-11-12
Product ID	1SBL347001N1211
EAN	3471523016644
Catalog Description	AF40N2-30-11-12 48-130V50/60HZ-DC Contactor
Long Description	<p>The AF40N2-30-11-12 is a 3 pole - 600 V UL, NEMA size N2 contactor with pre-mounted auxiliary contacts and Screw, switching power circuits up to 60 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (48-130 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.</p>

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900
Product Main Type	AF40N2

Popular Downloads

Instructions and Manuals	1SBC101036M6801
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	67 mm
Product Net Depth / Length	111 mm
Product Net Height	125.5 mm
Product Net Weight	1.01 kg

Technical

Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Rigid 1/2x 1 ... 2.5 mm ²
Connecting Capacity Control Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ²
Connecting Capacity Main Circuit	Flexible with Ferrule 1/2x 4 ... 35 mm ² Flexible with Insulated Ferrule 1/2x 4 ... 35 mm ² Rigid Stranded 1/2x 6 ... 35 mm ²
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 440 V 950 A cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 690 V 600 A
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-15) 1200 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 1200 cycles per hour (DC-13) 900 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Minimum Mounting Distance	Other Device Same Type, Horizontal 0 mm Other Device Same Type, Vertical 0 mm
Mounted Auxiliary Contacts	1 NO, 1 NC
Mounting Position	1, 1 +/-30°, 2, 3, 4, 5
Mounting by Screws (not supplied)	2 x M4 or 2 x M6 screws placed diagonally
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number of Main Contacts NC	0
Number of Main Contacts NO	3
Number of Poles	3
Operate Time	Between Coil De-energization and NC Contact Closing 19 ... 105 ms Between Coil De-energization and NO Contact Opening 17 ... 100 ms Between Coil Energization and NC Contact Opening 38 ... 95 ms Between Coil Energization and NO Contact Closing 42 ... 100 ms

Pollution Degree	3
Power Loss	at 6 A per Pole 0.1 W at Rated Operating Conditions AC-1 per Pole 3 W at Rated Operating Conditions AC-3 per Pole 1 W
Rated Control Circuit Voltage (U _c)	50 Hz 48 ... 130 V 60 Hz 48 ... 130 V DC Operation 48 ... 130 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Insulation Voltage (U _i)	acc. to IEC 60947-4-1 690 V acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Rated Operational Current AC-1 (I _e)	(690 V) 40 °C 70 A (690 V) 60 °C 60 A (690 V) 70 °C 50 A
Rated Operational Current AC-15 (I _e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Rated Operational Current AC-3 (I _e)	(415 V) 60 °C 40 A (440 V) 60 °C 40 A (500 V) 60 °C 35 A (690 V) 60 °C 25 A (380 / 400 V) 60 °C 40 A (220 / 230 / 240 V) 60 °C 40 A
Rated Operational Current AC-3e (I _e)	(415 V) 60 °C 40 A (440 V) 60 °C 40 A (500 V) 60 °C 35 A (690 V) 60 °C 25 A (380 / 400 V) 60 °C 40 A (220 / 230 / 240 V) 60 °C 40 A
Rated Operational Current DC-13 (I _e)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Rated Operational Power AC-3 (P _e)	(400 V) 18.5 kW (415 V) 22 kW (440 V) 22 kW (500 V) 22 kW (690 V) 22 kW (380 / 400 V) 18.5 kW (220 / 230 / 240 V) 11 kW
Rated Operational Power AC-3e (P _e)	(415 V) 22 kW (440 V) 22 kW (500 V) 22 kW (690 V) 22 kW (380 / 400 V) 18.5 kW (220 / 230 / 240 V) 11 kW
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Short-time Withstand Current Low Voltage (I _{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 600 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 110 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 250 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1000 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 350 A for 0.1 s 140 A

for 1 s 100 A

Standards	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60947-1, UL 60947-4-1, CSA C22.2 No. 60947-1:22, CSA C22.2 No. 60947-4-1:22
Terminal Type	Screw Terminals
Tightening Torque	Auxiliary Circuit 1.2 N-m Control Circuit 1.2 N-m Main Circuit 4 N-m
Wire Stripping Length	Auxiliary Circuit 10 mm Control Circuit 10 mm Main Circuit 16 mm

Technical UL/CSA

Connecting Capacity Control Circuit UL/CSA	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Connecting Capacity Main Circuit UL/CSA	Rigid Stranded 1/2x 10-2 AWG
Continuous Current Rating NEMA	45 A
Full Load Amps Motor Use	(120 V AC) Single Phase 3 A (200 ... 208 V AC) Three Phase 10 A (220 ... 240 V AC) Three Phase 15 A (240 V AC) Single Phase 7-1/2 A (440 ... 480 V AC) Three Phase 30 A (550 ... 600 V AC) Three Phase 40 A
General Use Rating UL/CSA	(600 V AC) 60 A
Horsepower Rating NEMA	(115 V AC) Single Phase 3 Hp (200 V AC) Three Phase 10 Hp (230 V AC) Single Phase 7-1/2 Hp (230 V AC) Three Phase 15 Hp (460 V AC) Three Phase 25 Hp (575 V AC) Three Phase 25 Hp
Maximum Operating Voltage UL/CSA	Main Circuit 600 V
NEMA Size	2
Pilot Duty UL/CSA	A600 Q600
Tightening Torque UL/CSA	Auxiliary Circuit 11 in-lb Control Circuit 11 in-lb Main Circuit 35 in-lb

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay -40 ... 70 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand	Category B according to IEC 60947-1 Annex Q
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40$ °C 105 A acc. to IEC 60947-5-1, $\Theta = 40$ °C 16 A
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: A 25 g Closed, Shock Direction: B1 25 g Closed, Shock Direction: B2 15 g Closed, Shock Direction: C1 25 g Closed, Shock Direction: C2 25 g Open, Shock Direction: A 25 g Open, Shock Direction: B1 5 g

Open, Shock Direction: B2 15 g
 Open, Shock Direction: C1 25 g
 Open, Shock Direction: C2 25 g

Resistance to Vibrations 3g Closed Position & 3g Open Position 5 ... 300 Hz

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE Category	Product Not in WEEE Scope

Circular Value

End of Life Instructions	1SBC101081M6801
--------------------------	-----------------

Certificates and Declarations

CB Certificate	CB_SE-113324
CCC Certificate	CQC2015010304824714
CQC Certificate	CQC2015010304824714 CQC2012010304589737
Declaration of Conformity - CCC	2020980304001256 2020980304001074
Declaration of Conformity - CE	1SBD250027U1000
Declaration of Conformity - UKCA	1SBD250056U1000
UL Certificate	UL-US-L312527-1141-10303102-9 UL-CA-L312527-4141-10303102-9
UL Listing Card	UL_E312527

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	150 mm
Package Level 1 Depth / Length	150 mm
Package Level 1 Height	97 mm
Package Level 1 Gross Weight	1.11 kg
Package Level 1 EAN	3471523016644
Package Level 3 Units	240 piece

Classifications

eClass	V11.0 : 27371003
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching

ETIM 8	EC000066 - Power contactor, AC switching
ETIM 9	EC000066 - Power contactor, AC switching
Object Classification Code	Q
UNSPSC	39121529

Categories

Low Voltage Products and Systems → Control Products → Contactors → NEMA Contactors

