



PRODUCT-DETAILS

OS630B03N3P**OS630B03N3P SWITCH FUSE****General Information**

| | |
|-----------------------|--|
| Extended Product Type | OS630B03N3P |
| Product ID | 1SCA100860R1001 |
| EAN | 6417019358024 |
| Catalog Description | OS630B03N3P SWITCH FUSE |
| Long Description | Switch Fuses,Front Operated,4-pole,03 (Left Side),British Standard,C1-C2,Handle and shaft included,Detachable Neutral Link Integrated Into the Mechanism |

Circular Value

| | |
|--------------------------------|---|
| Group Waste to Landfill Target | UL 2799 Zero Waste To Landfill Validation available |
|--------------------------------|---|

Eco Transparency

| | |
|---|-----------------|
| Environmental Product Declaration - EPD | 1SCC311202D0201 |
|---|-----------------|

Material Compliance

| | |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 1SCC011021D0201 |
| RoHS Information | 1SCC011020D0201 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA | 1SCC011025D0201 |

Ordering

| | |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85365080 |
| Country of Origin | Finland (FI) |

Popular Downloads

| | |
|---|-----------------|
| Data Sheet, Technical Information | 1SCC311013C0201 |
| Instructions and Manuals | 1SCC311016M0210 |
| Environmental Product Declaration - EPD | 1SCC311202D0201 |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width | 343 mm |
| Product Net Height | 306 mm |
| Product Net Depth / Length | 233 mm |
| Product Net Weight | 13.5 kg |

Technical

| | |
|--|--|
| Rated Operational Current AC-21A (I_e) | (500 V) 630 A (690 V) 630 A |
| Rated Operational Current AC-22A (I_e) | (380 ... 415 V) 630 A (500 V) 630 A (690 V) 630 A |
| Rated Operational Current AC-23A (I_e) | (380 ... 415 V) 630 A (500 V) 630 A (690 V) 630 A |
| Rated Operational Power AC-23A (P_e) | (220 ... 240 V) 200 kW (400 V) 355 kW (415 V) 355 kW (500 V) 450 kW (690 V) 630 kW |
| Conventional Free-air Thermal Current (I_{th}) | $\Theta = 40\text{ °C}$ 630 A |
| Conventional Thermal Current (I_{the}) | Fully Enclosed 570 A |
| Rated Impulse Withstand Voltage (U_{imp}) | 12 kV |
| Rated Insulation Voltage | 1000 V |

(U_i)

| | |
|---|---|
| Rated Operational Voltage | Main Circuit 690 V AC |
| Rated Short-time Withstand Current Low Voltage (I_{cw}) | for 1 s 18 kiloampere rms |
| Rated Conditional Short-Circuit Current (I_{nc}) | (690 V) 80 kA |
| Power Loss | at Rated Operating Conditions per Pole 46 W |
| Pollution Degree | 3 |
| Handle Type | Pistol handle and shaft included |
| Fourth Pole Type | Detachable Neutral Link Integrated Into the Mechanism |
| Switches Operating Mechanism | 03 (Left Side) |
| Position of Line Terminals | Top In - Bottom Out, Bottom In - Top Out |
| Fuse Size | C1-C2 |
| Fuse System | British Standard |
| Operating Mode | Front Operated |
| Standards | IEC 60947-3 |
| Special Functions | Detachable Neutral |
| Mounting Type | Base mounting |
| Number of Poles | 3 |
| Terminal Type | Lug terminals |
| Terminal Width | 39 mm |
| Tightening Torque | 50 ... 75 N·m |
| Rated Current (I_n) | Main Circuit 630 A |

Technical UL/CSA

| | |
|-------------------|---------------|
| Tightening Torque | 50 ... 75 N·m |
|-------------------|---------------|

Certificates and Declarations

| | |
|--------------------------------|-------------------------|
| A2L Certificate – IEC | 1SCC311209D0201 |
| ATEX Certificate | No certification needed |
| CCC Certificate | CCC OS630-800 2016 |
| Declaration of Conformity - CE | 1SCC311112D2704 |
| DNV GL Certificate | 1SCC311131D0203 |
| UL Certificate | No certification needed |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 328 mm |
| Package Level 1 Depth / Length | 365 mm |
| Package Level 1 Height | 260 mm |
| Package Level 1 Gross Weight | 13.5 kg |
| Package Level 1 EAN | 6417019358024 |

Classifications

| | |
|------------------------------------|--|
| Object Classification Code | Q |
| ETIM 8 | EC001040 - Fuse switch disconnecter |
| ETIM 9 | EC001040 - Fuse switch disconnecter |
| UNSPSC | 39122233 |
| IDEA Granular Category Code (IGCC) | 5291 >> Fuse switch disconnecter |
| eClass | V11.1 : 27371401 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Switches → Switch Fuses

