



 PRODUCT-DETAILS

OT32ELMM4BL

OT32ELMM4BL Enclosed Switch Disconnecter

"No longer for sale" replaced by OKA40S4G



General Information

Extended Product Type	OT32ELMM4BL
Product ID	1SCA105488R1001
EAN	6417019394534
Catalog Description	OT32ELMM4BL Enclosed Switch Disconnecter
Long Description	Enclosed Switch Disconnecter, 4-p. 400V AC22 40A, Steel sheet enclosure, Black Selector handle. Interlocked cover. Defeatable interlocking.

Material Compliance

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Replacement Product ID (NEW)	OKA40S4G

Country of Origin

Finland (FI)

Popular Downloads

Instructions and Manuals	1SCC340009C0201
--------------------------	-----------------

Dimensions

Product Net Width	166 mm
Product Net Height	245 mm
Product Net Depth / Length	150 mm
Product Net Weight	1.6 kg

Technical

Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 40 A (690 V) 40 A
Conventional Thermal Current (I_{the})	Fully Enclosed 40 A
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Handle Color	Black
Handle Type	Selector handle
Number of Poles	4
Cable Cross-Section	0.75 ... 10 mm ²
Cable Entry Position	Up/Down
Cable Outlets Per Side	2x ϕ 25.5+ ϕ 16.5 / 2x ϕ 25.5+ ϕ 16.5
Degree of Protection	acc. to IEC 60529 IP54
Enclosure Material	Steel sheet
Mounted Auxiliary Contacts	0 NO, 0 NC

Certificates and Declarations

Declaration of Conformity - CE	1SCC340001D2703
--------------------------------	-----------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	166 mm
Package Level 1 Depth / Length	245 mm
Package Level 1 Height	150 mm
Package Level 1 Gross Weight	1.6 kg
Package Level 1 EAN	6417019394534

Classifications

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors → Enclosed Switch-Disconnectors

