

PRODUCT-DETAILS

OXA1200U3X3QT OXA1200U3X3QT AUTOMATIC TRANSFER SWITCH



General Information	
Extended Product Type	OXA1200U3X3QT
Product ID	1SCA153563R1001
EAN	6417019845890
Catalog Description	OXA1200U3X3QT AUTOMATIC TRANSFER SWITCH
Long Description	The all-new TruONE is the world's first true purpose-built automatic transfer switch, engineered to incorporate switch and controller in one seamless unit. Performance tested beyond standard requirements, TruONE stands ready to ensure the steady delivery of critical power at all times. Its self-contained design reduces the number of wires and connections, which speeds installation and minimizes the potential for connection failures to ensure best-in-class reliability. Its predictive maintenance and modular components reduce downtime and service costs. And its advanced connectivity is ready for the future. Every TruONE features a wide voltage range from 200 to 480 VAC (with +/-20% tolerance), reducing the need to stock multiple SKUs, reducing inventory and saving space in the warehouse. Main characteristics of this particular TruONE type: Open style ATS, open transition type I-II operation, Level 3 controller (LCD)

ABB EcoSolutions

Subject to change without notice

2024/10/04

© 2024 ABB. All rights reserved.

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 69.6 %
End of Life Instructions	1SCC303064M020
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation availabl
Eco Transparency	
Environmental Product Declaration - EPD	1SCC303132D020
Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011022D020
RoHS Information	1SCC011023D020
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 201
Toxic Substances Control Act - TSCA	1SCC303119D020
Ordering Minimum Order Quantity	1 pieco
	85365080
Minimum Order Quantity Customs Tariff Number Country of Origin	1 piece 85365080 Finland (Fl
Minimum Order Quantity Customs Tariff Number	85365080 Finland (Fl
Minimum Order Quantity Customs Tariff Number Country of Origin Popular Downloads Data Sheet, Technical Information Instructions and	85365080 Finland (Fl 1SCC303008C020 1SCC303011M0201_FW2.0
Minimum Order Quantity Customs Tariff Number Country of Origin Popular Downloads Data Sheet, Technical Information Instructions and Manuals	85365080 Finland (Fl 1SCC303008C020 1SCC303011M0201_FW2.02 1SCC303011M0201_FW2.02 0X_800U-1600E_3X3_Tstg 1SCC308273F000 1SCC308272F000 1SCC308272F0000 1SCC308270F0000 1SCC308270F0000 1SCC308270F0000 1SCC308331F0000
Minimum Order Quantity Customs Tariff Number Country of Origin Popular Downloads Data Sheet, Technical Information Instructions and Manuals Mechanical Drawings	85365080 Finland (Fl 1SCC303008C020) 1SCC303011M0201_FW2.00 1SCC303011M0201_FW2.00 0X_800U-1600E_3X3_Tstg 1SCC308273F0000 1SCC308272F0000 1SCC308271F0000 1SCC308270F0000
Minimum Order Quantity Customs Tariff Number Country of Origin Popular Downloads Data Sheet, Technical	85365080 Finland (Fl 1SCC303008C020 1SCC303011M0201_FW2.0 1SCC303011M0201_FW2.0 0X_800U-1600E_3X3_T_stp 1SCC308273F000 1SCC308271F000 1SCC308271F000 1SCC308271F000 1SCC308270F000 1SCC308330F000 1SCC308330F000 Circuit diagram_0XA_Tdx

Dimensions

Product Net Width

© 2024 ABB. All rights reserved.

597 mm

Subject to change without notice

Yes

23.5 in
359 mm
14.13 in
212 mm
8.35 in
30.67 kg
67.62 lb

Technical	
Rated Operational Current AC-31B (I _e)	(200 415 V AC) 1600 A
Conventional Free-air Thermal Current (I _{th})	Θ = 40 °C 1600 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (Ui)	1000 V
Rated Operational Voltage	Main Circuit 200 480 V AC
Rated Frequency (f)	Main Circuit 50-60 Hz
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 0.1 s 65 kiloampere rms
Power Loss	at Rated Operating Conditions per Pole 23 W
Handle Type	Direct mounted handle
Position of Line Terminals	Supplies on Top - Load on Bottom
Standards	UL1008 / IEC60947-6-1
Controller Type	Level 3 (LCD)
Special Functions	Open style
Number of Poles	3
Degree of Protection	Front IP20
Terminal Type	Bolt
Transition Type	Open

Technical UL/CSA	
Ampere Rating	200-480V 1200 A

Certificates and Declarations	
Declaration of Conformity - CE	1SCC303063D2701
Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	430 mm
	16.93 in
Package Level 1 Depth /	690 mm
Length	

© 2024 ABB. All rights reserved.

Package Level 1 Height

2024/10/04

Subject to change without notice

450 mm 17.72 in

Package Level 1 Gross	43.67 kg
Weight	96.28 lb
Package Level 1 EAN	6417019845890

Classifications	
ETIM 8	EC000216 - Switch disconnector
ETIM 9	EC000216 - Switch disconnector (low voltage)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

 $\mathsf{Low}\ \mathsf{Voltage}\ \mathsf{Products}\ \mathsf{and}\ \mathsf{Systems} \to \mathsf{Switches} \to \mathsf{Change-over}\ \mathsf{and}\ \mathsf{Transfer}\ \mathsf{Switches} \to \mathsf{Automatic}\ \mathsf{Transfer}\ \mathsf{Switches}\ \mathsf{TruONE}$

