



 PRODUCT-DETAILS

E3V-A 800 PR122/P-LSI In=800A 3p W MP

E3V-A 800 PR122/P-LSI In=800A 3p W MP



General Information

| | |
|-----------------------|--|
| Extended Product Type | E3V-A 800 PR122/P-LSI In=800A 3p W MP |
| Product ID | 1SDA060869R1 |
| EAN | 8015644633929 |
| Catalog Description | E3V-A 800 PR122/P-LSI In=800A 3p W MP |
| Long Description | SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E3V-A 800A UL THREE-POLE OVERCURRENT RELEASE PR122/P-LSI R800 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED |

Environmental

| | |
|---------------------------|----------------|
| Environmental Information | 9AKK10103A6076 |
|---------------------------|----------------|

Material Compliance

| | |
|-------------------|--|
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Conflict Minerals
Reporting Template
(CMRT)

Document availability on demand

Ordering

| | |
|------------------------|---------------|
| EAN | 8015644633929 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 432 mm |
| Product Net Height | 461 mm |
| Product Net Depth / Length | 396.5 mm |
| Product Net Weight | 64 kg |

Additional Information

| | |
|-------------------|---------------------|
| Product Main Type | SACE Emax |
| Product Name | Air Circuit Breaker |
| Product Type | CBMP |
| Version | W |

Technical

| | |
|---------------------------------|--|
| Current Type | AC |
| Electrical Durability | Ue = < 508 V 10000 cycle Ue = 508 ... 635 V 10000 cycle 30 cycles per hour |
| Mechanical Durability | 15000 cycle 30 cycles per hour |
| Number of Poles | 3 |
| Power Loss | at Rated Operating Conditions per Pole 37 W |
| Rated Current (I _n) | 800 A |
| Rated Voltage (U _r) | 600 V |
| Release | PR122/P-LSI |
| Release Type | EL |
| Short-Circuit Performance Level | V |
| Standards | UL 1066 |
| Sub-type | E3 |

Technical UL/CSA

| | |
|------------------------------------|---|
| Interrupting Rating acc. to UL1066 | (240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA |
|------------------------------------|---|

Certificates and Declarations

| | |
|-----------------------|-----------------|
| Data Sheet, Technical | 1SDC200008D0202 |
|-----------------------|-----------------|

Information

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 1SDL000165R0015 |
| Instructions and Manuals | 1SDH000532R0002 |

Classifications

| | |
|---------------|--|
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
|---------------|--|

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax

