



PRODUCT-DETAILS

E3V-A 3200 PR121/P-LI In=3200 3p F VR<HR

E3V-A 3200 PR121/P-LI In=3200 3p F VR<HR



General Information	
Extended Product Type	E3V-A 3200 PR121/P-LI In=3200 3p F VR<HR
Product ID	1SDA060883R1
EAN	8015644634063
Catalog Description	E3V-A 3200 PR121/P-LI In=3200 3p F VR<HR
Long Description	SACE EMAX CIRCUIT-BREAKER E3V-A 3200A UL THREE-POLE FIXED WITH TERMINALS REAR VERTICAL OVERCURRENT RELEASE PR121/P-LI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Environmental	
Environmental Information	9AKK10103A6076

Material Compliance	
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template	Document availability on demand

(CMRT)

**Ordering**

EAN	8015644634063
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

**Dimensions**

Product Net Width	404 mm
Product Net Height	418 mm
Product Net Depth / Length	302 mm
Product Net Weight	60 kg

**Container Information**

Package Level 1 EAN	8015644609139
---------------------	---------------

**Additional Information**

Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	CB
Version	F

**Technical**

Current Type	AC
Electrical Durability	U <sub>e</sub> =< 508 V 8000 cycle U <sub>e</sub> = 508 ... 635 V 8000 cycle 30 cycles per hour
Mechanical Durability	15000 cycle 30 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 330 W
Rated Current (I <sub>n</sub> )	3200 A
Rated Operational Current (I <sub>e</sub> )	3200 A
Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
Rated Uninterrupted Current (I <sub>u</sub> )	3200 A
Rated Voltage (U <sub>r</sub> )	600 V
Release	PR121/P-LI
Release Type	EL
Short-Circuit Performance Level	V
Standards	UL 1066
Sub-type	E3
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Orientated

---

## Technical UL/CSA

---

Interrupting Rating acc. to UL1066	(240 V AC) 125 kA (480 V AC) 125 kA (600 V AC) 100 kA
------------------------------------	---

---

---

## Certificates and Declarations

---

Data Sheet, Technical Information	1SDC200008D0202
Declaration of Conformity - CE	1SDL000165R0015
Instructions and Manuals	1SDH000532R0002

---

---

## Classifications

---

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

---

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax

