



 PRODUCT-DETAILS

X1N1000PR332/PLIIn=1000A4pFF

X1N 1000 PR332/P LI In=1000A 4p F F



General Information

Extended Product Type	X1N1000PR332/PLIIn=1000A4pFF
Product ID	1SDA062401R1
EAN	8015644649470
Catalog Description	X1N 1000 PR332/P LI In=1000A 4p F F
Long Description	C.BREAKER EMAX X1N 1000 FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR332/P-LI R 1000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Environmental

Environmental Information	1SDC200009D0201
---------------------------	-----------------

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Conflict Minerals
Reporting Template
(CMRT)

Document availability on demand

Ordering

EAN	8015644649470
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	280 mm
Product Net Height	268 mm
Product Net Depth / Length	181 mm
Product Net Weight	14 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	360 mm
Package Level 1 Height	350 mm
Package Level 1 Depth / Length	360 mm
Package Level 1 Gross Weight	15.5 kg
Package Level 1 EAN	8015644609139

Additional Information

Product Main Type	SACE Emax
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	F

Technical

Current Type	AC
Electrical Durability	Ue = < 440 V 4000 cycle Ue = 500 ... 690 V 2000 cycle 30 cycles per hour
Mechanical Durability	12500 cycle 60 cycles per hour
Number of Poles	4
Power Loss	79 W
Rated Current (I _n)	1000 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Current (I _e)	1000 A

Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 50 kA (230 V AC) 50 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 42 kA (660 V AC) 42 kA (690 V AC) 42 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 42 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(220 V AC) 65 kA (230 V AC) 65 kA (380 V AC) 65 kA (400 V AC) 65 kA (415 V AC) 65 kA (440 V AC) 65 kA (500 V AC) 50 kA (660 V AC) 50 kA (690 V AC) 50 kA
Rated Uninterrupted Current (I_u)	1000 A
Rated Voltage (U_r)	690 V
Release	PR332/P LI
Release Type	EL
Short-Circuit Performance Level	N
Standards	IEC
Sub-type	X1
Terminal Connection Type	Fixed Circuit-Breakers Front

Certificates and Declarations

Data Sheet, Technical Information	1SDC200009D0203
Declaration of Conformity - CE	1SDL000165R0018
Instructions and Manuals	1SDH000606R0004 1SDH000587R0002

Classifications

Object Classification Code	Q
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax

