



PRODUCT-DETAILS

DR LJ25R 2500 4p to E2.2/MS int**DR LJ25R 2500 4p to E2.2/MS int****General Information**

Extended Product Type	DR LJ25R 2500 4p to E2.2/MS int
Product ID	1SDA121025R1
EAN	8056221156158
Catalog Description	DR LJ25R 2500 4p to E2.2/MS int
Long Description	Direct Replacement LJ25R 2500 4p to E2.2/MS - Service customization

Technical

Standards	IEC
Current Type	AC
Rated Voltage (U_r)	690 V
Rated Operational Voltage	690 V AC
Rated Current (I_n)	2500 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 42 kA
Number of Poles	4

Version	W
Configuration Type	Mounted only
Product Type	Direct Replacement GE EntelliGuard L to Emax 2 IEC
Sub-type	E2.2
Operational Derating	Derating to 2400A in case of cassettes with vertical (VR) terminals. Derating to 2300A in case of cassettes with horizontal (HR) or front (F) terminals

Material Compliance

RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration	9AKK108466A1425
Conflict Minerals Reporting Template (CMRT)	Document availability on demand

Dimensions

Product Net Width	418 mm
Product Net Height	374 mm
Product Net Depth / Length	376 mm

Ordering

Package Level 1 Units	pallet (lift) 1 piece
EAN	8056221156158

Installation

Instructions and Manuals	1SDH002096A1001
Wiring Diagram	1SDM000047A1001

Popular Downloads

Data Sheet, Technical Information	1SDC200118L0201
-----------------------------------	-----------------

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85362090

Additional Information

Product Main Type	Low Voltage retrofit with Emax 2
-------------------	----------------------------------

Categories

Low Voltage Products and Systems → Service → Extensions, Upgrades and Retrofits → Retrofits