



PRODUCT-DETAILS**DR F4B/MS 3200 3p CD CCC to E4.2/MS int****DR F4B/MS 3200 3p CD CCC to E4.2/MS int**

General Information

Extended Product Type	DR F4B/MS 3200 3p CD CCC to E4.2/MS int
Product ID	1SDA127343R1
EAN	8056221297103
Catalog Description	DR F4B/MS 3200 3p CD CCC to E4.2/MS int
Long Description	Direct Replacement F4B/MS 3200 3p Closed Door CCC to E4.2/MS - Service customization

Eco Transparency

Environmental Product Declaration - EPD	1SDH002332A1001
---	-----------------

Technical

Standards	CCC
Current Type	AC
Rated Voltage (U _r)	690 V

Rated Operational Voltage	690 V AC
Rated Current (I _n)	3200 A
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 55 kA
Number of Poles	3
Version	W
Configuration Type	Mounted only
Product Type	Direct Replacement ABB Megamax to Emax 2 CCC
Sub-type	E4.2

Material Compliance

RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration	9AKK108466A1425
Conflict Minerals Reporting Template (CMRT)	Document availability on demand

Dimensions

Product Net Width	519 mm
Product Net Height	406 mm
Product Net Depth / Length	583 mm

Ordering

Package Level 1 Units	pallet (lift) 1 piece
EAN	8056221297103

Installation

Instructions and Manuals	1SDH002018A1001
Wiring Diagram	1SDM000111R0001

Popular Downloads

Data Sheet, Technical Information	1SDC001043L0205
-----------------------------------	-----------------

Classifications

WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85362090

Additional Information

Product Main Type

Low Voltage retrofit with Emax 2

Categories

Low Voltage Products and Systems → Service → Extensions, Upgrades and Retrofits → Retrofits