



PRODUCT-DETAILS

# D4S 630 TMF630/6000 F F 3P

## D4S 630 TMF630/6000 F F 3P



### General Information

Extended Product Type	D4S 630 TMF630/6000 F F 3P
Product ID	1SDA127856R1
EAN	8056221291712
Catalog Description	D4S 630 TMF630/6000 F F 3P
Long Description	C.BREAKER SACE FORMULA BLD D4S 630 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 630-6000 A

### Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

### Ordering

EAN	8056221291712
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

## Dimensions

Product Net Width	139.5 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	3.25 kg

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	245 mm
Package Level 1 Height	230 mm
Package Level 1 Depth / Length	287 mm
Package Level 1 Gross Weight	4.85 kg
Package Level 1 EAN	8056221291712

## Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Product Main Type	SACE FORMULA BLD
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Version	F

## Technical

Current Type	AC
Electrical Durability	5000 cycle 60 cycles per hour
Mechanical Durability	15000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 41 W
Rated Current ( $I_n$ )	630 A
Rated Frequency (f)	50/60 Hz
Rated Impulse Withstand Voltage ( $U_{imp}$ )	6 kV
Rated Insulation Voltage ( $U_i$ )	690 V AC
Rated Operational Voltage	500 V AC
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(380 V AC) 50 kA (415 V AC) 50 kA (500 V AC) 12.5 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(380 V AC) 50 kA (415 V AC) 50 kA (500 V AC) 25 kA
Rated Uninterrupted Current ( $I_u$ )	630 A
Rated Voltage ( $U_r$ )	500 V AC
Release	TMF

Release Type	TM
Short-Circuit Performance Level	S
Standards	IEC
Sub-type	D4
Terminal Connection Type	Front

---

## Classifications

---

ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Formula BLD

