





---

 PRODUCT-DETAILS

# D1B 125 TMF16/400 F F 4P

## D1B 125 TMF16/400 F F 4P




---

**General Information**

Extended Product Type	D1B 125 TMF16/400 F F 4P
Product ID	1SDA127857R1
EAN	8056221291729
Catalog Description	D1B 125 TMF16/400 F F 4P
Long Description	C.BREAKER SACE FORMULA BLD D1B 125 FIXED FOUR-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 16-400 A

---

**Material Compliance**

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

## Ordering

EAN	8056221291729
Minimum Order Quantity	1 piece
Customs Tariff Number	85362010

## Dimensions

Product Net Width	101.6 mm
Product Net Height	130 mm
Product Net Depth / Length	64 mm
Product Net Weight	0.925 kg

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	111 mm
Package Level 1 Height	125 mm
Package Level 1 Depth / Length	137 mm
Package Level 1 Gross Weight	1.05 kg
Package Level 1 EAN	8056221291729

## Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Product Main Type	SACE FORMULA BLD
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Version	F

## Technical

Current Type	AC
Electrical Durability	4000 cycle 120 cycles per hour
Mechanical Durability	10000 cycle 120 cycles per hour
Number of Poles	4
Power Loss	at Rated Operating Conditions per Pole 2.8 W
Rated Current ( $I_n$ )	16 A
Rated Frequency (f)	50/60 Hz
Rated Impulse Withstand Voltage ( $U_{imp}$ )	6 kV
Rated Insulation Voltage ( $U_i$ )	690 V AC
Rated Operational Voltage	500 V AC
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(380 V AC) 9 kA (415 V AC) 9 kA (500 V AC) 2.5 kA

Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(380 V AC) 18 kA (415 V AC) 18 kA (500 V AC) 5 kA
Rated Uninterrupted Current ( $I_u$ )	125 A
Rated Voltage ( $U_r$ )	500 V AC
Release	TMF
Release Type	TM
Short-Circuit Performance Level	B
Standards	IEC
Sub-type	D1
Terminal Connection Type	Front

### Classifications

ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

### Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Formula BLD

