




---

 PRODUCT-DETAILS

# XLP00-A60/60-B-3BC-below

## XLP00-A60/60-B-3BC-below Fuse Switch Disconnecter




---

**General Information**

Extended Product Type	XLP00-A60/60-B-3BC-below
Product ID	1SEP101916R0001
EAN	7025840015635
Catalog Description	XLP00-A60/60-B-3BC-below Fuse Switch Disconnecter
Long Description	XLP00.3-pole.160A. incl. A60/60 adapter and 3 Bridge Clamps. cable below

---

**Material Compliance**

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

---

**Popular Downloads**

Data Sheet, Technical Information	1SEC312012D0201
-----------------------------------	-----------------

Instructions and Manuals

No Instructions and Manuals needed

---

**Environmental**


---

Degree of Protection IP30

---

**Ordering**


---

Minimum Order Quantity	1 piece
Customs Tariff Number	85389099
Country of Origin	Bulgaria (BG) China (CN)

---



---

**Dimensions**


---

Product Net Width	105 mm
Product Net Height	206 mm
Product Net Depth / Length	126 mm
Product Net Weight	0.95 kg

---



---

**Container Information**


---

Package Level 1 Units	shrink-wrap 1 piece
Package Level 1 Width	105 mm
Package Level 1 Depth / Length	126 mm
Package Level 1 Height	206 mm
Package Level 1 Gross Weight	0.95 kg
Package Level 1 EAN	7025840015635
Package Level 2 EAN	7025840015635

---



---

**Technical**


---

Rated Operational Current AC-21B ( $I_e$ )	(690 V) 125 A
Rated Operational Current AC-22B ( $I_e$ )	(500 V) 160 A (800 V) 63 A (1000 V) 125 A
Rated Operational Current AC-23B ( $I_e$ )	(400V) 125 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	Main Circuit 8 kV
Rated Operational Voltage	400 V AC 500 V AC 690 V AC 800 V AC 1000 V AC
Rated Frequency (f)	Main Circuit 50/60 Hz
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(690 V) 50 kiloampere rms
Power Loss	at Rated Load 3.5 W
Handle Type	Front cover 3P
Fuse Size	NH00 NH000
Fuse System	DIN
Standards	IEC60947-3

Special Functions	GB/T14048.3 Not Included
Mounting Type	60mm Busbar System
Number of Poles	3
Degree of Protection	IP30
Terminal Type	Cable Clamp
Device Type Manager (DTM)	Fuseswitchdisconnector
Rated Current ( $I_n$ )	160 A
Rated Voltage ( $U_r$ )	400 V AC 500 V AC 690 V AC 800 V AC 1000 V AC
Electronic Fuse Monitoring	No

## Certificates and Declarations

Declaration of Conformity - CE	1SEP500050P0001
--------------------------------	-----------------

## Classifications

Object Classification Code	S
ETIM 8	EC001040 - Fuse switch disconnector
ETIM 9	EC001040 - Fuse switch disconnector
eClass	V11.1 : 27371401
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Norway)	1687115

## Categories

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → EasyLine

