



## PRODUCT-DETAILS

# XLP2-2P-4BC

## XLP2-2P-4BC Fuse Switch Disconnecter



### General Information

Extended Product Type	XLP2-2P-4BC
Product ID	1SEP600123R0002
EAN	7025840086697
Catalog Description	XLP2-2P-4BC Fuse Switch Disconnecter
Long Description	XLP2,2-pole,400A, incl. 4 Bridge Clamps

### Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

### Popular Downloads

Data Sheet, Technical	1SEC312012D0201
-----------------------	-----------------

## Information

Instructions and Manuals	No Instructions and Manuals needed
--------------------------	------------------------------------

---

**Environmental**

Degree of Protection	IP30
----------------------	------

---

**Ordering**

Minimum Order Quantity	1 piece
Customs Tariff Number	85389099
Country of Origin	China (CN)

---

**Dimensions**

Product Net Width	160 mm
Product Net Height	129 mm
Product Net Depth / Length	289 mm
Product Net Weight	2.49 kg

---

**Container Information**

Package Level 1 Units	shrink-wrap 1 piece
Package Level 1 Width	160 mm
Package Level 1 Depth / Length	289 mm
Package Level 1 Height	129 mm
Package Level 1 Gross Weight	2.49 kg
Package Level 1 EAN	7025840086697
Package Level 2 EAN	7025840086697

---

**Technical**

Rated Operational Current AC-21B ( $I_e$ )	(690 V) 315 A
Rated Operational Current AC-22B ( $I_e$ )	(500 V) 400 A
Rated Operational Current DC-22B	(440 V) 400 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	Main Circuit 8 kV
Rated Operational Voltage	440 V DC 500 V AC 690 V AC
Rated Frequency (f)	Main Circuit 50/60 Hz
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(690 V) 50 kiloampere rms
Power Loss	at Rated Load 13 W
Handle Type	Front cover 2P
Fuse Size	NH2

Fuse System	DIN
Standards	IEC60947-3 GB/T14048.3
Special Functions	Not Included
Mounting Type	Baseplate
Number of Poles	2
Degree of Protection	IP30
Terminal Type	Cable Clamp
Device Type Manager (DTM)	Fuseswitchdisconnector
Rated Current (I <sub>n</sub> )	400 A
Rated Voltage (U <sub>r</sub> )	440 V DC 500 V AC 690 V AC
Electronic Fuse Monitoring	No

## Certificates and Declarations

Declaration of Conformity - CE	1SEP500050P0001
--------------------------------	-----------------

## Classifications

Object Classification Code	S
ETIM 8	EC001040 - Fuse switch disconnector
ETIM 9	EC001040 - Fuse switch disconnector
eClass	V11.1 : 27371401
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Norway)	1687821
E-Number (Sweden)	3171967

## Categories

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → EasyLine

