

PRODUCT-DETAILS





General Information	
Global Commercial Alias	MLT41
Extended Product Type	MLT41
Product ID	1TQR162004Z0100
EAN	not available
Catalog Description	Main Lug Kit
Long Description	ReliaGear lighting panelboards are factory assembled on rigid steel frames and equipped with circuit breakers from 15 A to 800 A. The maximum fully-rated short circuit rating is equal to 65 kAIC to 240 V AC and 480/277 V AC.

ABB EcoSolutions	
ABB EcoSolutions	Yes
Circular Design Principles Recyclability Rate	92.6 %
Offered with Extended Lifetime	Product Modularity
End of Life Instructions	1SQC173021M0202
Environmental Product	1SQC173004D0201

© 2024 ABB. All rights reserved.

2024/10/15

Subject to change without notice

## Declaration - EPD

Technical	
Rated Voltage (Ur)	480 V AC
Rated Current (In)	400 V AC
Model Number	MLT41
Number of Poles	3
Cable Cross-Section	750 kcmil
Connecting Capacity Main Circuit	750 kcmil
Terminal Type	Lug terminals

Dimensions	
Product Net Width	0.001 in
Product Net Height	0.001 in
Product Net Depth / Length	0.001 in
Product Net Weight	8.000 lb
Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	variable Ib
Certificates and Declarations	
Declaration of Conformity - CE	No declaration needed
Installation	
Instructions and	No document needed

Instructions and Manuals

## **Popular Downloads**

Data Sheet, Technical Information

9AKK107680A9334

Classifications		
ETIM 8	EC002021 - Terminal block connector	
ETIM 9	EC002021 - Terminal block connector	
WEEE Category	Product Not in WEEE Scope	
UNSPSC	39121446	
eClass	V11.1 : 27141151	
IDEA Granular Category Code (IGCC)	4666 >> Wire terminal connector kit	

© 2024 ABB. All rights reserved.

## Categories

Low Voltage Products and Systems  $\rightarrow$  NEMA Residential and Commercial Portfolio  $\rightarrow$  Lighting Panels & Breakers  $\rightarrow$  PROSTOCK Lighting Panels

