

PRODUCT-DETAILS





General Information	
Global Commercial Alias	AF37SP
Extended Product Type	AF37SP
Product ID	1TQR337100D0000
EAN	not available
Catalog Description	Front
Long Description	ReliaGear lighting panelboards are factory assembled on rigid steel frames and equipped with circuit breakers from 15 A to 800 A. The maximum fully-rated short circuit rating is equal to 65 kAIC to 240 V AC and 480/277 V AC.

ABB EcoSolutions	
ABB EcoSolutions	Yes
Circular Design Principles Recyclability Rate	92.6 %
Offered with Extended Lifetime	Product Modularity
End of Life Instructions	1SQC173021M0202
Environmental Product	1SQC173004D0201

© 2024 ABB. All rights reserved.

2024/10/15

Subject to change without notice

Declaration - EPD

Technical	
Surface Finishing	Powder coating
Enclosure Material	Steel
Material	Steel

Dimensions	
Product Net Width	508 mm
Product Net Height	953 mm
Product Net Depth / Length	0.100 in
Product Net Weight	23.000 lb

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	30.90 lb
Certificates and Declarations	
Declaration of Conformity - CE	No declaration needec
Installation	
Instructions and Manuals	No document needed
Popular Downloads	
Data Sheet, Technical Information	No document needed
Classifications	
ETIM 8	EC000456 - Front panel (enclosure/cabinet)
ETIM 9	EC000456 - Front panel (enclosure/cabinet,
WEEE Category	Product Not in WEEE Scope

WEEE Category UNSPSC eClass IDEA Granular Category Code (IGCC)

39121321 V11.1 : 27182806

4465 >> Enclosure General Accessories

Categories

Low Voltage Products and Systems \rightarrow NEMA Residential and Commercial Portfolio \rightarrow Lighting Panels & Breakers \rightarrow ReliaGear Lighting Panels

