

PRODUCT-DETAILS

AF37FDM

Front



General Information	
Global Commercial Alias	AF37FDM
Extended Product Type	AF37FDM
Product ID	1TQR337200F0300
EAN	not available
Catalog Description	Front
Long Description	ReliaGear lighting panelboards are factory assembled on rigid steel frames and equipped with circuit breakers from 15 A to 800 A. The maximum fully-rated short circuit rating is equal to 65 kAIC to 240 V AC and 480/277 V AC.

ABB EcoSolutions	
ABB EcoSolutions	Yes
Circular Design Principles Recyclability Rate	92.6 %
Offered with Extended Lifetime	Product Modularity
End of Life Instructions	1SQC173021M0202
Environmental Product	1SQC173004D0201

AF37FDM 2/3

Declaration - EPD

Dimensions	
Product Net Width	21.250 in
Product Net Height	37.500 in
Product Net Depth / Length	0.100 in
Product Net Weight	24.000 lb

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	31.90 lb

Declaration of No declaration neede	Certificates and Declarations	
Conformity - CE		No declaration needed

Installation	
Instructions and	No document needed
Manuals	

Popular Downloads	
Data Sheet, Technical	9AKK107680A9334
Information	

Classifications	
WEEE Category	Product Not in WEEE Scope
UNSPSC	39121321
IDEA Granular Category Code (IGCC)	4465 >> Enclosure General Accessories

Categories

AF37FDM 3/3

 $Low\ Voltage\ Products\ and\ Systems \rightarrow NEMA\ Residential\ and\ Commercial\ Portfolio \rightarrow Lighting\ Panels\ \&\ Breakers \rightarrow ReliaGear\ Lighting\ Panels$

