



PRODUCT-DETAILS

AF82FDTUMW**Front****General Information**

Global Commercial Alias	AF82FDTUMW
Extended Product Type	AF82FDTUMW
Product ID	1TQR382235F2300
Catalog Description	Front
Long Description	ReliaGear lighting panelboards are factory assembled on rigid steel frames and equipped with circuit breakers from 15 A to 800 A. The maximum fully-rated short circuit rating is equal to 65 kAIC to 240 V AC and 480/277 V AC.

Dimensions

Product Net Width	31.250 in
Product Net Height	83.750 in
Product Net Depth / Length	0.100 in
Product Net Weight	78.000 lb

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	99.870 lb

Certificates and Declarations

Declaration of Conformity - CE	No declaration needed
--------------------------------	-----------------------

Installation

Instructions and Manuals	No document needed
--------------------------	--------------------

Popular Downloads

Data Sheet, Technical Information	No document needed
-----------------------------------	--------------------

Classifications

WEEE Category	Product Not in WEEE Scope
UNSPSC	39121321
IDEA Granular Category Code (IGCC)	4465 >> Enclosure General Accessories

Categories

Low Voltage Products and Systems → NEMA Residential and Commercial Portfolio → Lighting Panels & Breakers → ReliaGear Lighting Panels



