AF88SDN 1/3



PRODUCT-DETAILS

AF88SDN

Front



General Information	
Global Commercial Alias	AF88SDN
Extended Product Type	AF88SDN
Product ID	1TQR388100F1000
EAN	not available
Catalog Description	Front
Long Description	ReliaGear lighting panelboards are factory assembled on rigid steel frames and equipped with circuit breakers from 15 A to 800 A. The maximum fully-rated short circuit rating is equal to 65 kAIC to 240 V AC and 480/277 V AC.

ABB EcoSolutions	
ABB EcoSolutions	Yes
Circular Design Principles Recyclability Rate	92.6 %
Offered with Extended Lifetime	Product Modularity
End of Life Instructions	1SQC173021M0202
Environmental Product	1SQC173004D0201

AF88SDN 2/3

Declaration - EPD

Dimensions	
Product Net Width	20.000 in
Product Net Height	88.500 in
Product Net Depth / Length	0.100 in
Product Net Weight	55.000 lb

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	71.850 lb

	Certificates and Declarations	
Conformity - CE	Declaration of Conformity - CE	No declaration needed

Installation	
Instructions and	No document needed
Manuals	

Popular Downloads	
Data Sheet, Technical	No document needed
Information	

Classifications	
WEEE Category	Product Not in WEEE Scope
UNSPSC	39121321
IDEA Granular Category Code (IGCC)	4465 >> Enclosure General Accessories

Categories

AF88SDN 3/3

 $Low\ Voltage\ Products\ and\ Systems \rightarrow NEMA\ Residential\ and\ Commercial\ Portfolio \rightarrow Lighting\ Panels\ \&\ Breakers \rightarrow ReliaGear\ Lighting\ Panels$



