9T10K4010G86 1/3



PRODUCT-DETAILS

9T10K4010G86 Low Voltage Dry Type Transformer-LPT



General Information	
Global Commercial Alias	9T10K4010G86
Extended Product Type	9T10K4010G86
Product ID	1TQX252721L0271
EAN	783173365755
Catalog Description	Low Voltage Dry Type Transformer-LPT
Long Description	ABB's Drive Isolation Transformers (DIT) are designed to specifically handle the mechanical stresses, voltage distortions, and harmonics associated with silicon-controlled rectifiers (SCR) or Thyristor applications. Drive Isolation Transformers have symmetrically placed taps and added coil bracing to withstand the mechanical forces caused by severe SCR or thyristor duty cycles. These features also help to protect the transformer from the regenerative duty and more frequent momentary short-circuits associated with SCR commutation. The 9T10K4xxxGxx Drive Isolation Transformers are UL and cUL and bear the third party cUL Energy Verfied mark showing these produts comply with the NRCan

Technical	
Suitable for Isolation	Yes
Primary Voltage	575 V AC
Secondary Voltage	325Y V AC 188 V AC
Primary Rated Impulse	10 kV

9T10K4010G86 2/3

Withstand Voltage	
Frequency (f)	60 Hz
Apparent Power Output	145 kV·A
Connection Configuration	Delta Primary
N. J. CDI	Wye Secondary
Number of Phases	320 °C Class B
Insulation Class Surge Suppression	220 °C,Class R Not Included
Accessory Type	Rain Shields
7.0000001, 17,00	Lug Kit
E I T NEMA	Ground Kit
Enclosure Type NEMA	Type2
Transformer Type Housing Material	Drive Isolation Painted Steel
Material of Conductor	Aluminum
Accessories Available	Yes
Color	ANSI 61 Grey
Number of Batteries	0
Product Frame Size	DY76A
Temperature Rise	150 °C
Material Compliance	
RoHS Status	No declaration needed
REACH Information	No data - If REACH inform is not yet available for a certain product
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Environmental Ambient Temperature Degree of Protection	40 °C Housing IP20
Technical UL/CSA	
Enclosure Type UL/CSA	2
Dimensions	
Product Net Width	37.3 in 947.5 mm
Product Net Height	45.8 in 1163.4 mm
Product Net Depth /	24 in 609.6 mm
Length Product Net Weight	947 lb
	429.6 kg
Dimension Diagram	303B111CADYP76A
Ordering	
Package Level 1 Units	pallet (lift) 1 piece
Package Level 1 Gross	1008 lb
Weight	457.3 kg

9T10K4010G86 3/3

No declaration needed
9AKK107991A214 <u>2</u>
9AKK107680A9377

Classifications		
ETIM 8	EC004582 - Low voltage dry type transformer	
ETIM 9	EC004582 - Low voltage dry type transformer	
WEEE Category	Product Not in WEEE Scope	
WEEE B2C / B2B	Business To Business	
UNSPSC	39121029	
IDEA Granular Category Code (IGCC)	4124 >> Distribution power transformers	
Object Classification Code	TA	

Categories

 $\mbox{Low Voltage Products and Systems} \rightarrow \mbox{NEMA Residential and Commercial Portfolio} \rightarrow \mbox{LV Dry Type Transformers} \rightarrow \mbox{Large Power Transformers}$





