




PRODUCT-DETAILS

1VCF337173R0121

VD4/ZH 17.06.16 P150



General Information

Product ID	1VCF337173R0121
Catalog Description	VD4/ZH 17.06.16 P150

Certificates and Declarations

Data Sheet, Technical Information	1VCP000001_A
Instructions and Manuals	647654

Dimensions

Product Net Weight	116 kg
--------------------	--------

Additional Information

Rated Voltage (U _r)	17,5 kV
---------------------------------	---------

Rated Impulse Withstand Voltage (U_{imp})	95 kV
Power Frequency Withstand Voltage	38 kV
Rated Frequency (f)	50/60 Hz
Rated Current (I_n)	630 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 3 s 16 kA
Rated Short-Circuit Capacity	16 kA DC Component 30 %
Rated Short-Circuit Making Capacity (I_{cm})	40 kA
Rated Cable-Charging Breaking Current	31,5 A
Operating Sequence	O-0,3S-CO-15S-CO
Suitable for Product Class	M2
Ambient Temperature	-5 ... 40 °C
Product Main Type	VD4
Product Name	VD4/ZH 17.06.16 P150
Distance Between Phases	150 mm

Categories

Medium Voltage Products and Systems → Circuit Breakers → Indoor Vacuum Circuit Breakers

