



PRODUCT-DETAILS

1VCF337261R0141**VD4/ZS8 12.06.25 P150****General Information**

Product ID	1VCF337261R0141
Catalog Description	VD4/ZS8 12.06.25 P150

Certificates and Declarations

Data Sheet, Technical Information	1VCP000001_A
Instructions and Manuals	647654
Dimension Diagram	1VCD000091

Dimensions

Product Net Weight	116 kg
--------------------	--------

Additional Information

Rated Voltage (U_r)	12 kV
Rated Impulse Withstand Voltage (U_{imp})	75 kV
Power Frequency Withstand Voltage	28 kV
Rated Frequency (f)	50/60 Hz
Rated Current (I_n)	630 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 3 s 25 kA
Rated Short-Circuit Capacity	25 kA DC Component 30 %
Rated Short-Circuit Making Capacity (I_{cm})	63 kA
Rated Cable-Charging Breaking Current	25 A
Operating Sequence	O-0,3S-CO-15S-CO
Suitable for Product Class	M2
Ambient Temperature	-5 ... 40 °C
Product Main Type	VD4
Product Name	VD4/ZS8 12.06.25 P150
Distance Between Phases	150 mm

Categories

Medium Voltage Products and Systems → Circuit Breakers → Indoor Vacuum Circuit Breakers

