



 PRODUCT-DETAILS

1VCF337655R0654

VD4/SA55 36.25.32 P280 185BIL



General Information

Product ID	1VCF337655R0654
Catalog Description	VD4/SA55 36.25.32 P280 185BIL

Certificates and Declarations

Data Sheet, Technical Information	1VCP000001_A
Instructions and Manuals	647654
Dimension Diagram	GCEM700198

Dimensions

Product Net Weight	380 kg
--------------------	--------

Additional Information

Rated Voltage (U_r)	36 kV
Rated Impulse Withstand	185 kV

Voltage (U_{imp})	
Power Frequency Withstand Voltage	95 kV
Rated Frequency (f)	50/60 Hz
Rated Current (I_n)	2500 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 3 s 31,5 kA
Rated Short-Circuit Capacity	31,5 kA DC Component 25 %
Rated Short-Circuit Making Capacity (I_{cm})	82 kA
Rated Cable-Charging Breaking Current	50 A
Operating Sequence	O-0,3S-CO-15S-CO
Suitable for Product Class	M2
Ambient Temperature	-5 ... 55 °C
Product Main Type	VD4
Product Name	VD4/SA55 36.25.32 P280 185BIL
Distance Between Phases	280 mm

Categories

Medium Voltage Products and Systems → Circuit Breakers → Indoor Vacuum Circuit Breakers

