



PRODUCT-DETAILS**1VCF370325R0355****VD4-CS 36.12.32 P360 50HZ**

General Information

Product ID	1VCF370325R0355
Catalog Description	VD4-CS 36.12.32 P360 50HZ

Certificates and Declarations

Data Sheet, Technical Information	1VCP000771
Instructions and Manuals	1VCD601693
Dimension Diagram	2RDA038365

Dimensions

Product Net Weight	235 kg
--------------------	--------

Additional Information

Standards	IEC 62271-100
Rated Voltage (U_r)	36 kV
Rated Impulse Withstand Voltage (U_{imp})	185 kV
Power Frequency Withstand Voltage	95 kV
Rated Frequency (f)	50/60 Hz
Rated Current (I_n)	1250 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 3 s 31,5 kA
Rated Short-Circuit Capacity	31,5 kA DC Component 30 %
Rated Short-Circuit Making Capacity (I_{cm})	95 kA
Operating Sequence	CO-15S-CO
Suitable for Product Class	M2 C2
Ambient Temperature	-5 ... 40 °C
Product Main Type	VD4-CS
Product Name	VD4-CS 36.12.32 P360 50HZ
Distance Between Phases	360 mm

Categories

Medium Voltage Products and Systems → Circuit Breakers → Indoor Vacuum Circuit Breakers

