



---

**PRODUCT-DETAILS**

# UniSec STOCK-SA25

## UniSec, type STOCK-SA25



---

**General Information**

Extended Product Type	UniSec STOCK-SA25
Product ID	1VCF838000R5125
Catalog Description	UniSec, type STOCK-SA25

---

**Certificates and Declarations**

Data Sheet, Technical Information	1VFM200003
Installation Manual	1VFM200004
Operating Manual	1VFM200005
Standards	IEC 62271-200

---

**Additional Information**

Product Name	UniSec, type STOCK-SA25
Marketing Description	Pre-engineered switchgear compliant with CEI 0-16 with fast delivery timing, compact dimension, high performances and safety for operators

---

**Ordering**


---

Product Main Type	Medium Voltage Switchgear
-------------------	---------------------------

---



---

**Technical**


---

Rated Voltage ( $U_r$ )	24 kV
Power Frequency Withstand Voltage	50 kV
Rated Impulse Withstand Voltage ( $U_{imp}$ )	125 kV
Rated Current ( $I_n$ )	630 A
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 16 kA
Maximum Peak Current	40 kA
Rated Frequency (f)	50/60 Hz
Internal Arc Classification	AF For1s 16 kA
Auxiliary Voltage AC/DC	230 V AC
Ambient Temperature	-5 ... 40 °C

---



---

**Categories**


---

Medium Voltage Products and Systems → Switchgear and Motor Control → IEC - Secondary Air Insulated Switchgear → UniSec



