



PRODUCT-DETAILS

BMS414B63 Miniature Circuit Breaker



General Information	
Extended Product Type	BMS414B63
Product ID	2CDS644041R0635
EAN	4016779048842
Catalog Description	Miniature Circuit Breaker
Long Description	The basic M MCB series protects installations against overloads and short-circuits, guaranteeing reliability and safety of operations. ABB basic M series satisfies most common requirements in terms of MCBs, allowing the usage of different pole configurations, characteristics and rated currents for residential and commercial applications. This product is manufactured according to international IEC standards.

Technical	
Standards	IEC 60898-1
Tripping Characteristic	В
Rated Operational	acc. to IEC 60898-1 400 V
Voltage	acc. to IEC 60947-2 440 V
Rated Insulation Voltage (Ui)	acc. to IEC/EN 60664-1 440 V

© 2024 ABB. All rights reserved.

Subject to change without notice

Rated Impulse	
Withstand Voltage (Uim	р
)	

)	
Input Voltage Type	AC
Rated Current (In)	63 A
Rated Short-Circuit Capacity	(AC) 4.5 kA (400 V AC) 4.5 kA
Rated Frequency (f)	50 / 60 Hz
Energy Limiting Class	3
Electrical Endurance	4000 AC cycle
Mechanical Endurance	10000 cycle
Number of Protected Poles	4
Number of Poles	4
Overvoltage Category	
Tightening Torque	2 N·m
Actuator Type	Toggle
Actuator Marking	I / O
Recommended Screw Driver	Pozidriv 2
Accessories Available	Yes
Connecting Capacity	Flexible 1 25 mm² Rigid 1 35 mm²
Wire Stripping Length	12.5 mm

Material Compliance

RoHS Information	2CDK400667D0201
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20170816
REACH Declaration	9AKK107492A1906
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20240821
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Ambient Air	Operation -25 +55 °C
Temperature	Storage -40 +70 °C
Degree of Protection	IP20
	Enclosure with Cover IP40
Pollution Degree	2

Dimensions	
Width in Number of Modular Spacings	4.0
Product Net Width	70 mm
Product Net Height	88 mm
Product Net Depth / Length	69 mm
Product Net Weight	372 g
Built-In Depth (t ₂)	69 mm

© 2024 ABB. All rights reserved.

2024/10/17 Subject to change without notice

4 kV

Ordering	
Package Level 1 Units	3 piece
Package Level 1 Gross Weight	1.293 kg
Certificates and Declarations	
Declaration of Conformity - CE	2CDK400666D270
Installation	
Instructions and Manuals	No document needed
Popular Downloads Data Sheet, Technical	9AKK107045A1496
Information	
Classifications	
ETIM 8	EC000042 - Miniature circuit breaker (MCB
ETIM 9	EC000042 - Miniature circuit breaker (MCB
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm
WEEE B2C / B2B	Business To Business
CN8	8536 20 10
UNSPSC	39121603
eClass	V11.0 : 2714190
IDEA Granular Category Code (IGCC)	4897 >> Miniature circuit breaker

Categories

 $\mathsf{Low}\ \mathsf{Voltage}\ \mathsf{Products}\ \mathsf{and}\ \mathsf{Systems} \to \mathsf{Modular}\ \mathsf{DIN}\ \mathsf{Rail}\ \mathsf{Products} \to \mathsf{Basic}\ \mathsf{M}\ \mathsf{System} \to \mathsf{Miniature}\ \mathsf{Circuit}\ \mathsf{Breakers}\ \mathsf{MCBs}$

