6197/15-101 1/3



PRODUCT-DETAILS

## 6197/15-101

## 6197/15-101 Uni Dim Actuator 4x600W/VA



General Information	
Extended Product Type	6197/15-101
Product ID	2CKA006197A0035
EAN	4011395163658
Catalog Description	6197/15-101 Uni Dim Actuator 4x600W/VA
Long Description	Multichannel universal dimming actuator for controlling incandescent lamps, 230 V incandescent halogen lamps, low-voltage halogen lamps with conventional or electronic transformers, and dimmable energy-saving halogen lamps. Optimized for dimming of Philips retrofit LEDs (LEDi). Increasing the max. load via channel bridging possible. The outputs can be switched parallel in any combination. Outputs automatically recognise the connected load. In addition, the operating mode can be selected manually. Status indication of the channels via LED. Direct manual operation with / without KNX voltage connected or in an unprogrammed status possible. Incl. 10 logic channels (light scene actuator, sequence actuator, logic gates, etc.).

Installation	
Instructions and Manuals	DEBJE-0173-1-7794
Wiring Diagram	2CKA000097E0125
Mounting Type	DIN-Rail

6197/15-101 2/3

Environmental	
Ambient Air	Operation -5 +45 °C
Temperature	
Degree of Protection	IP20
Technical	
Data Sheet, Technical Information	2CKA001373B7795
Number of Outputs	4
Compatible Bus Systems	KNX (TP)
Product Range	KNX
Number of Batteries	C
Floctrical	
Electrical  Rated Voltage (U <sub>r</sub> )	230 V
	230 \
Rated Voltage (U <sub>r</sub> ) Rated Operational	230 V
Rated Voltage (U <sub>r</sub> ) Rated Operational Voltage	230 V 230 V 230 V AC/DC
Rated Voltage (U <sub>r</sub> ) Rated Operational Voltage Auxiliary Voltage AC/DC	230 V 230 V 230 V AC/DC 50 / 60 H:
Rated Voltage (U <sub>r</sub> ) Rated Operational Voltage Auxiliary Voltage AC/DC Rated Frequency (f)	230 V 230 V 230 V AC/DC 50 / 60 Hz
Rated Voltage (U <sub>r</sub> ) Rated Operational Voltage Auxiliary Voltage AC/DC Rated Frequency (f)	230 V 230 V 230 V AC/DC 50 / 60 Hz
Rated Voltage (U <sub>r</sub> ) Rated Operational Voltage Auxiliary Voltage AC/DC Rated Frequency (f) Load Type	230 V 230 V 230 V AC/DC 50 / 60 Hz Universa
Rated Voltage (U <sub>r</sub> ) Rated Operational Voltage Auxiliary Voltage AC/DC Rated Frequency (f) Load Type  Dimensions Width in Number of	230 V 230 V 230 V AC/DC 50 / 60 Hz Universa

Materia	

RoHS Information	2CKA200000E4763
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

## **Certificates and Declarations**

Declaration of	2CKA100000E1309
Conformity - CE	

			ons
•	 •	-	 

ETIM 9	EC001094 - Dimming actuator for bus sys	
eClass	V11.0 : 27143123	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
WEEE B2C / B2B	Business To Consumer	

6197/15-101 3/3

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow KNX \rightarrow Lighting\ Control \rightarrow Universal\ Dim\ Actuators$ 

