

PRODUCT-DETAILS

# ID FH202 AC-25/0.3

# ID FH202 AC-25/0.3 Residual Current Circuit Breaker 2P Type AC 300 mA



General Information	
Extended Product Type	ID FH202 AC-25/0.3
Product ID	2CSF202013R3250
EAN	8012542046615
Catalog Description	ID FH202 AC-25/0.3 Residual Current Circuit Breaker 2P Type AC 300 mA
Long Description	The RCCBs FH200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous AC and A types is particularly suitable for installation in domestic applications.

Technical	
Standards	IEC 61008
Type of Residual Current	Type AC
Rated Voltage (U <sub>r</sub> )	230 V
Rated Operational Voltage	230 V
Rated Insulation Voltage (U <sub>1</sub> )	500 V
Rated Impulse Withstand Voltage (U <sub>imp</sub>	1 kV

ID FH202 AC-25/0.3 2/4

)	
Dielectric Test Voltage	2500 V
Rated Current (In)	25 A
Rated Residual Current	300 mA
Rated Conditional Short- Circuit Current (Inc)	6 kA
Maximum Surge Current	0.25 kA
Leakage Current Type	AC
Rated Frequency (f)	50 Hz
Electrical Endurance	10000 cycle
Mechanical Endurance	20000 cycle
Number of Poles	2
Number of Modular Spacings per DIN Rail	2
Operating Characteristic	Instantaneous
Tightening Torque	2.8 N·m
Mounting Type	DIN-Rail
Options Provided	None
Rated Cross-Section	1 - Solid-Core 025 mm² 4 - Multi-Wired 025 mm²

Material Compliance	
RoHS Information	9AKK106713A5603
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20211115
REACH Declaration	9AKK108467A9482
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240429
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Ambient Air	Operation -5 +40 °C
Temperature	Storage -40 +70 °C
Degree of Protection	IP2X
Environmental Information	Refer to RoHS

Technical UL/CSA	
Short-Circuit Current	300 mA
Rating (SCCR)	

Dimensions	
Width in Number of Modular Spacings	2
Product Net Width	35 mm
Product Net Height	69 mm
Product Net Depth / Length	85 mm

ID FH202 AC-25/0.3 3/4

Product Net Weight 0.2 kg
Built-In Depth (t<sub>2</sub>) 69 mm

## **Ordering**

Package Level 1 Units box 1 piece
Package Level 1 Gross 0.236 kg
Weight

#### **Certificates and Declarations**

Declaration of 9AKK106713A5603 Conformity - CE

#### Installation

Instructions and No document needed Manuals

#### **Popular Downloads**

Data Sheet, Technical 2CSC400030D0202
Information 2CSC400030D0202

#### Classifications

ETIM 8	EC000003 - Residual current circuit breaker (RCCB)
ETIM 9	EC000003 - Residual current circuit breaker (RCCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363030
eClass	V11.0 : 27142201
Object Classification Code	F

### **Categories**

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Modular\ DIN\ Rail\ Products\ \rightarrow\ Residual\ Current\ Devices\ RCDs$ 

ID FH202 AC-25/0.3 4/4





