



 PRODUCT-DETAILS

F202 A S-100/0.3

F202 A S-100/0.3 Residual Current Circuit Breaker 2P Type A 300 mA



General Information

| | |
|-----------------------|--|
| Extended Product Type | F202 A S-100/0.3 |
| Product ID | 2CSF202201R3900 |
| EAN | 8012542916109 |
| Catalog Description | F202 A S-100/0.3 Residual Current Circuit Breaker 2P Type A 300 mA |
| Long Description | The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. |

ABB EcoSolutions

| | |
|---|---|
| ABB EcoSolutions | Yes |
| EcoSolutions Profile | 9AKK108469A3794 |
| Circular Design Principles Recyclability Rate | Design for Closing Resource Loops - Standard EN45555 - 52.5 % |
| Group Waste to Landfill Target | No non-hazardous waste is sent to a landfill |
| Sustainable Material Content in Packaging | Recycled Paper - 78 % |

| | |
|---|--------------------|
| Offered with Extended Lifetime | Product Durability |
| End of Life Instructions | 9AKK108468A4361 |
| Environmental Product Declaration - EPD | 9AKK108467A3700 |

Technical

| | |
|--|---|
| Standards | IEC/EN 61008 UL 1053 |
| Type of Residual Current | Type A |
| Rated Voltage (U_r) | 230 V |
| Rated Operational Voltage | 230 V |
| Rated Insulation Voltage (U_i) | 500 V |
| Test Voltage (U_t) | 110-254 V |
| Rated Impulse Withstand Voltage (U_{imp}) | 4 kV |
| Input Voltage Type | AC |
| Rated Current (I_n) | 100 A |
| Rated Residual Current | 300 mA |
| Rated Conditional Short-Circuit Current (I_{nc}) | 10 kA |
| Maximum Surge Current | 5 kA |
| Leakage Current Type | A |
| Frequency (f) | 50/60 Hz |
| Rated Frequency (f) | 50 ... 60 Hz |
| Power Loss | at Rated Operating Conditions per Pole 6.5 W |
| Power Supply Connection | Arbitrary |
| Electrical Endurance | 10000 cycle |
| Number of Poles | 2 |
| Number of Modular Spacings per DIN Rail | 2 |
| Operating Characteristic | Selective |
| Tightening Torque | 2.8 N·m |
| Accessory Type | Auxiliary contact Signal / auxiliary contact Shunt trip Auto re-closing units Motor operating device Overvoltage release Undervoltage release |
| Mounting Type | DIN-Rail |
| Options Provided | None |
| Mounting Position | Any |
| Accessories Available | Yes |
| Connecting Capacity | Busbar 10 mm ² Rigid 35 ... 35 mm ² Flexible 35 ... 35 mm ² |
| Rated Cross-Section | 4 - Multi-Wired 0...35 mm ² 1 - Solid-Core 35...35 mm ² |
| Wire Stripping Length | Top 12.7 mm Bottom 14.9 mm |
| Terminal Type | Screw Terminals |

Material Compliance

| | |
|---|--|
| RoHS Information | 9AKK106713A5602 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date | 20211115 |
| REACH Declaration | 9AKK108467A9482 |
| REACH Information | True - contains substances > 0.1 mass percentage |
| REACH Date | 20240429 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |
| SCIP | 18f132b0-8f03-4611-9c59-dba03cc369bf Italy (IT) |

Environmental

| | |
|--|---|
| Ambient Air Temperature | Operation -25 ... 55 °C Storage -40 ... 70 °C |
| Degree of Protection | IP2X |
| Pollution Degree | 2 |
| Resistance to Vibrations | 20 Cycles with Load 0.8 In: 1g or 1mm 50 ... 150 ... 5 Hz |
| Resistance to Shock acc. to IEC 60068-2-27 | 25g 2 shocks 13 ms |
| Environmental Information | Refer to RoHS |

Technical UL/CSA

| | |
|-------------------------------------|----------|
| Maximum Operating Voltage UL/CSA | 277 V AC |
| Short-Circuit Current Rating (SCCR) | 300 mA |

Dimensions

| | |
|-------------------------------------|-------|
| Width in Number of Modular Spacings | 2 |
| Product Net Width | 35 mm |
| Product Net Height | 85 mm |
| Product Net Depth / Length | 69 mm |
| Product Net Weight | 200 g |
| Built-In Depth (t ₂) | 69 mm |

Ordering

| | |
|------------------------------|-------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Gross Weight | 0.235 kg |
| E-Number (Norway) | 1630578 |

Certificates and Declarations

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 9AKK106713A5602 |
|--------------------------------|-----------------|

Installation

Instructions and
Manuals9AKK107991A6127

Popular Downloads

Data Sheet, Technical
Information9AKK107991A8329

Classifications


| | |
|---------------------------------------|--|
| ETIM 8 | EC000003 - Residual current circuit breaker (RCCB) |
| ETIM 9 | EC000003 - Residual current circuit breaker (RCCB) |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 85363030 |
| UNSPSC | 39121601 |
| eClass | V11.0 : 27142201 |
| IDEA Granular Category Code (IGCC) | 4875 >> Residual current circuit breaker (RCCB) |
| Object Classification Code | F |

Accessories

| Identifier | Description | Type | Quantity | Unit Of Measure |
|-----------------|----------------------------|---------------|----------|-----------------|
| 2CDS200912R0001 | Auxiliary Contact | S2C-H6R | 2 | piece |
| 2CDS200922R0001 | Signal / Auxiliary Contact | S2C-S/H6R | 2 | piece |
| 2CDS200946R0001 | Auxiliary Contact | S2C-H6-11R | 1 | piece |
| 2CDS200946R0003 | Auxiliary Contact | S2C-H6-02R | 1 | piece |
| 2CDS200946R0002 | Auxiliary Contact | S2C-H6-20R | 1 | piece |
| 2CSS200933R0011 | Shunt trip | F2C-A1 | 1 | piece |
| 2CSS200933R0012 | Shunt trip | F2C-A2 | 1 | piece |
| 2CSS200911R0005 | Undervoltage Release | S2C-UA 230 AC | 1 | piece |
| 2CSS200911R0007 | Undervoltage Release | S2C-UA 24 DC | 1 | piece |
| 2CSS200911R0002 | Undervoltage Release | S2C-UA 24 AC | 1 | piece |
| 2CSS200911R0008 | Undervoltage Release | S2C-UA 48 DC | 1 | piece |
| 2CSS200911R0004 | Undervoltage Release | S2C-UA 110 AC | 1 | piece |
| 2CSS200911R0006 | Undervoltage Release | S2C-UA 400 AC | 1 | piece |
| 2CSS200911R0001 | Undervoltage Release | S2C-UA 12 DC | 1 | piece |
| 2CSS200911R0010 | Undervoltage Release | S2C-UA 230 DC | 1 | piece |
| 2CSS200911R0009 | Undervoltage Release | S2C-UA 110 DC | 1 | piece |
| 2CSS200911R0003 | Undervoltage Release | S2C-UA 48 AC | 1 | piece |
| 2CSS200910R0005 | Oversvoltage Release | S2C-OVP1 | 1 | piece |
| 2CSS200993R0005 | Oversvoltage Release | S2C-OVP2 | 1 | piece |
| 2CSF201998R0034 | Autoreclosing unit | F3C-AR24 | 1 | piece |
| 2CSF202998R0034 | Autoreclosing unit | F3C-AR230 | 1 | piece |
| 2CSS201998R0033 | Motor Operating Device | S3C-MOD24 | 1 | piece |
| 2CSS202998R0033 | Motor Operating Device | S3C-MOD230 | 1 | piece |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Devices RCDs



360°

