




---

 PRODUCT-DETAILS

## ACS580-01-06A0-4

LV AC general purpose wall-mounted drive,  
UL: Pld 3 Hp, 6 A, 500 V (ACS580-01-06A0-4)




---

### General Information

Global Commercial Alias	ACS580-01-06A0-4
Product ID	3AUA0000204808
ABB Type Designation	ACS580-01-06A0-4
EAN	6438177450672

Catalog Description	LV AC general purpose wall-mounted drive, UL: Pld 3 Hp, 6 A, 500 V (ACS580-01-06A0-4)
---------------------	---

Long Description	<p>The wall-mounted ACS580-01 is available as UL Type 1 (IP21), Type 12 (IP55) and Type 4X (IP66) designed for OEM and end users who value high quality and robustness in their applications. Coated control boards, high enclosure classes, and motor temperature monitoring ensure processes will run smoothly even in harsh conditions.</p> <p>This drive is part of ABB's all-compatible drives portfolio, sharing the same control panel, PC tools, parameter structure and communications options as the ACS380/180 and ACS880. Learn it once; use it everywhere. With both V/Hz and sensorless vector control supporting most motor types such as induction, permanent magnet, synchronous reluctance, and optimum pole motors the ACS580 is ideal for use on compressors, conveyors, pumps, extruders, centrifuges, mixers, fans and other variable and constant torque applications, in a variety of industries, including food and beverage, plastic, textile, material handling, and agriculture.</p>
------------------	--

---

### Ordering

Country of Origin	United States (US)
Customs Tariff Number	85044080
Invoice Description	ACS580-01-06A0-4, PLd 3HP, I2LD 6A
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

**Dimensions**

Product Net Weight	11 lb
Product Net Depth / Length	8.78 in
Product Net Height	14.69 in
Product Net Width	4.82 in
Package Level 1 Units	1 carton

**Technical**

Number of Phases	3
Degree of Protection	IP21
Enclosure Type NEMA	Type1
Frequency (f)	50/60 Hz
Frame Size	R1
Input Voltage (U <sub>in</sub> )	525 ... 600 V
Mounting Type	Wall-mounting
Apparent Power Output	5.0 kV-A
Efficiency Level	IE2
Standby Loss	15 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	43 W	0.9 %	86.0 %
0 / 50 %	49 W	1.0 %	91.3 %
0 / 100 %	64 W	1.3 %	93.7 %
50 / 25 %	45 W	0.9 %	92.5 %
50 / 50 %	52 W	1.0 %	95.3 %
50 / 100 %	71 W	1.4 %	96.5 %
90 / 50 %	56 W	1.1 %	97.2 %
90 / 100 %	79 W	1.6 %	97.8 %

Temperature Rating	Maximum 40 °C
--------------------	---------------

**Technical UL**

Output Current, Heavy-Duty Use (UL)	4 A
Output Current, Light-Overload Use (UL)	6 A
Output Power, Heavy-Duty Use (UL)	3 Hp
Output Power, Light-	3 Hp

Overload Use (UL)

---

---

### Classifications

---

UNSPSC

39122001

---

---

### Environmental

---

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

---

---

### Additional Information

---

Product Name

AC Drive

---

---

### Categories

---

Drives → Low Voltage AC Drives → General Purpose Drives → ACS580-01 - Wall-mounted drive

