




PRODUCT-DETAILS

3GAA082314-CSE

IE2 High Efficiency Aluminum Motors, 0.75 kW,
400 V (3GAA082314-CSE)

**General Information**

| | |
|----------------------|--|
| Product ID | 3GAA082314-CSE |
| ABB Type Designation | M3AA 80D 4 |
| Catalog Description | IE2 High Efficiency Aluminum Motors, 0.75 kW, 400 V (3GAA082314-CSE) |

Ordering

| | |
|-------------------------|-----------------------------|
| ABB Type Designation | M3AA 80D 4 |
| Invoice Description | M3AA 80D 4 |
| Product Name | 3-Phase squirrel cage motor |
| Product Type | 3AA2_M3AA_IE2_AA |
| Made To Order | No |
| Minimum Order Quantity | 1 piece |
| Order Multiple | 1 piece |
| Selling Unit of Measure | piece |
| Country of Origin | Poland (PL) Romania (RO) |
| Customs Tariff Number | 85015100 |
| Stocked At | Menden, Germany |

| | |
|--------------------|--|
| (Warehouses) | Vittuone, Italy |
| Medium Description | 0.75kW, 4 Poles, Frame Size 80, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB14/IM3601 Mounting (3GAA082314-CSE) |
| Short Description | 0.75kW, 4P, Frame Size 80, 3PH, 400V, 50Hz, IP55, IMB14/IM3601 |

Electrical

Electrical Data

| Conn | Temp Class | Freq | Voltage | Power | Speed | Current | Power Factor | Efficiency | Torque | IS/IN |
|------|------------|-------|---------|---------|------------|---------|--------------|------------|----------|-------|
| Y | -- | 50 Hz | 400 V | 0.75 kW | 1415 r/min | 1.65 A | 0.820 | 79.80 % | 5.00 N·m | 5.90 |
| D | -- | 50 Hz | 230 V | 0.75 kW | 1415 r/min | 2.87 A | 0.820 | 79.80 % | 5.00 N·m | 5.90 |
| Y | -- | 60 Hz | 460 V | 0.75 kW | 1730 r/min | 1.62 A | 0.700 | 82.60 % | 4.10 N·m | 7.00 |

| | |
|----------------------------------|---|
| Connection Configuration | Y |
| Temperature Class Default | -- |
| Input Voltage (U _{in}) | 400 V |
| Frequency (f) | 50 Hz |
| Output Power | 0.75 kW |
| Altitude | 1000 m |
| Ambient Temperature | 40 °C |
| IC Class | IC411 |
| IE Class Data (50 Hz) | IE Class IE2 Full Load (100%) 79.8 % Partial Load (75%) 81.3 % Partial Load (50%) 79.9 % |
| IE Class Data (60 Hz) | IE Class IE2 Full Load (100%) 82.6 % Partial Load (75%) 82.5 % Partial Load (50%) 79.8 % |
| IP Class | IP55 |
| Insulation Class | ICLF |
| Direction of Rotation | Both sides |
| Number of Poles (High) | 4 |
| Two Speed Motor | No |
| Type of Duty | S1 |
| Voltage Code | S |

Mechanical

| | |
|-------------------------|--------------|
| Frame Material | Aluminum |
| Frame Size | 80 |
| Bearing | 6204-2Z/C3 |
| Bearing NDE | 6203-2Z/C3 |
| Lubrication | For life |
| IM Class | IMB14 IM3601 |
| Terminator Box Location | Top |

Dimensions

| | |
|-----------------------|----------|
| Package Level 1 Units | 0 carton |
|-----------------------|----------|

| | |
|----------------------------|----------|
| Product Net Depth / Length | 292.5 mm |
| Product Net Height | 193.5 mm |
| Product Net Width | 154 mm |
| Product Net Weight | 10 kg |
| Gross Weight | 13 kg |

Environmental

| | |
|---------------|--|
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| SCIP | 27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI) |

Classifications

| | |
|-----------|-------------|
| Standards | IEC 60034-1 |
| UNSPSC | 26101100 |

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

