



 PRODUCT-DETAILS

3GBA252042-BDG

No Description Available

General Information

Product ID	3GBA252042-BDG
ABB Type Designation	M2BA 250SMA 4
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M2BA 250SMA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6215-2Z/C3
Bearing NDE	6212-2Z/C3
Country of Origin	China (CN) Sweden (SE) Poland (PL)
Customs Tariff Number	85015290
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor
D	--	50 Hz	400 V	55.00 kW	1478 r/min	99.80 A	0.850
Y	--	50 Hz	690 V	55.00 kW	1478 r/min	57.90 A	0.850
D	--	50 Hz	415 V	55.00 kW	1480 r/min	99.70 A	0.820
D	--	60 Hz	460 V	55.00 kW	1782 r/min	86.30 A	0.850

Frame Material	Cast Iron
Frame Size	250
Gross Weight	373 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 93.5 % Partial Load (75%) 94.0 % Partial Load (50%) 93.4 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 94.0 % Partial Load (75%) 94.1 % Partial Load (50%) 93.0 %
IM Class	IMB5 IM3001
IP Class	IP55

Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Moment of Inertia	0.00000 kg/m³
Number of Poles (High)	4
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	363 kg
Product Type	2BA2_M2BA_IE2_CI
Quote Only	No
Replaced Product ID (OLD)	3GBA252041-BDG
Selling Unit of Measure	piece
Service Factor	0.00
Standards	IEC 60034-1
Starting of Motor	Direct Online
Stocked At (Warehouses)	Shanghai, China
Temperature Class Default	--
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)