06H404W679G2 1/10

PRODUCT-DETAILS

06H404W679G2

5HP,2900 75C RISERPM,3PH,50HZ,184T,0634M

General Information	
Global Commercial Alias	06H404W679G2
Product ID	7B06H404W679G2
ABB Type Designation	5HP,2900 75C RISERPM,3PH,50HZ,184T,
Catalog Description	5HP,2900 75C RISERPM,3PH,50HZ,184T,0634M

Additional Information	
ABB Type Designation	5HP,2900 75C RISERPM,3PH,50HZ,184T,
Ambient Temperature	40 °C
Brand / Label	Baldor-Reliance
Certification Agency	CSA UL
Country of Origin	United States (US)
Customs Tariff Number	85015220
Efficiency Level	IE3
Electrical Data	

Current

Enclosure Type	XPFC
Frame Material	Iron
Frame Size	Undefined
Global Commercial Alias	06H404W679G2
Gross Volume	7561.383 in ³
Gross Weight	141 lb
Invoice Description	5HP,2900 75C RISERPM,3PH,50HZ,184T,0634M
Made To Order	No
Medium Description	Frame Size 184T, 3 Phase, XPFC Enclosure,
Minimum Order Quantity	1 piece
Motor Base Type	Rigid
Motor Frame Size	184T

06H404W679G2 2/10



Freq

06H404W679G2 3/10

Power

06H404W679G2 4/10

Speed

06H404W679G2 5/10

Voltage

06H404W679G2 6/10

NEMA Design Code	A
Number of Phases	3
Number of Speeds	Single Speed
Order Multiple	1 piece
Product Name	LV Explosion Proof Motors
Product Net Depth / Length	26.375 in
Product Net Height	17.375 in
Product Net Weight	141 lb
Product Net Width	16.5 in
Product Type	Undefined
Quote Only	No
Selling Unit of Measure	piece
Service Factor	1.15
Short Description	Frame Size 184T, 3 PH, XPFC,
Standards	NEMA
Starting of Motor	Y-Start/Delta Run
Stocked At	China
(Warehouses)	Alabama, United States Alaska, United States
UNSPSC	26101115

06H404W679G2 7/10

06H404W679G2 8/10

06H404W679G2 9/10

06H404W679G2

10/1