




---

 PRODUCT-DETAILS

# 36F472S268G1

## 5//3HP,1750//1450RPM,3PH,60//50HZ,184TC

---

**General Information**

Global Commercial Alias	36F472S268G1
Product ID	7B36F472S268G1
ABB Type Designation	5//3HP,1750//1450RPM,3PH,60//50HZ,1
Catalog Description	5//3HP,1750//1450RPM,3PH,60//50HZ,184TC

---

**Additional Information**

ABB Type Designation	5//3HP,1750//1450RPM,3PH,60//50HZ,1
Ambient Temperature	40 °C
Brand / Label	Baldor-Reliance
Certification Agency	CSA CSA EEV UL UR
Country of Origin	United States (US)
Customs Tariff Number	85015220
Efficiency Level	IE3 Not Regulated / Exempt Premium Efficiency (NEMA 12-12)

**Electrical Data**

Current	Freq	Power	Speed	Voltage
13.4 A	60 Hz	5 Hp	1750 r/min	230 V
6.7 A	60 Hz	5 Hp	1750 r/min	460 V

Enclosure Type	XPFC
Frame Material	Steel
Frame Size	Undefined
Global Commercial Alias	36F472S268G1
Gross Volume	7192.91 in <sup>3</sup>
Gross Weight	108 lb
Invoice Description	5//3HP,1750//1450RPM,3PH,60//50HZ,184TC
Made To Order	No
Medium Description	Frame Size 184Tc, 3 Phase, XPFC Enclosure,

Minimum Order Quantity	1 piece
Motor Base Type	Rigid
Motor Frame Size	184TC
NEMA Design Code	B
Number of Phases	3
Number of Speeds	Single Speed
Order Multiple	1 piece
Product Name	LV Explosion Proof Motors
Product Net Depth / Length	26.625 in
Product Net Height	16.25 in
Product Net Weight	108 lb
Product Net Width	16.625 in
Product Type	Undefined
Quote Only	No
Selling Unit of Measure	piece
Service Factor	1.00
Short Description	Frame Size 184Tc, 3 PH, XPFC,
Standards	NEMA
Starting of Motor	Direct On Line
Stocked At (Warehouses)	China Alabama, United States Alaska, United States
UNSPSC	26101112