36G510X288G1 1/3




PRODUCT-DETAILS

36G510X288G1

General Purpose Motor 6 Hp 230 V (36G510X288G1)





General Information	
Global Commercial Alias	36G510X288G1
Product ID	7B36G510X288G1
ABB Type Designation	6HP,1725RPM,1PH,60HZ,184T,3646LC,OD
Catalog Description	General Purpose Motor 6 Hp 230 V (36G510X288G1)

Additional Information		
ABB Type Designation	6HP,1725RPM,1PH,60HZ,184T,3646LC,OD	
Ambient Temperature	40 °C	
Bearing	6206, Ball	
Bearing NDE	6205	
Brake Present	No	
Brand / Label	Baldor-Reliance®	
Catalog Number	36G510X288G1	
Certification Agency	CSA UR	
Country of Origin	United States (US)	
Customs Tariff Number	85015220	

36G510X288G1 2/3

Drive End Flange Type Standard

Efficiency Level Not Regulated / Exempt

Electrical Data

Current	Freq	Power	Speed	Voltage	
26 A	60 Hz	6 Hp	1725 r/min	230 V	
Enclosure Type					
Frame Material				9	
Frame Size				Undef	
Frequency (f)				6	
Global Commercial Alias				36G510X28	
Gross Volume				5274.13	
Gross Weight				3274.13	
Insulation Class					
			6HD 1725DDM 1	DU 60U7 104T 2646LC ODT	
Invoice Description			0HP,1725RPM,1	PH,60HZ,184T,3646LC,ODT	
Made To Order		C	- 1011 0 6110 1000 1	DN4 F 6' 104T 6+	
Medium Description		General Purposi	General Purpose 1PH Open, 6 HP, 1800 RPM, Frame Size 184T, Standar Mounting, 1 Phase, 230 V, 60 Hz (36G510X288G		
Minimum Order Quantity				1 p	
Motor Base Type				Foot Mou	
Motor Frame Size				:	
Mounting Orientation				Horizo	
Mounting Position					
NEMA Design Code					
Number of Phases					
Number of Poles					
Number of Poles (High)					
Number of Speeds				single_sp	
Order Multiple				1 p	
Output Power					
Power Factor				Ç	
Product Name				General Purpose 1PH C	
Product Net Depth / Length				21.6	
Product Net Height				15.1	
Product Net Weight				9	
Product Net Width				16.1	
Product Type				Undef	
Quote Only					
Rated Current (In)					
Rated Efficiency					
Rated Speed				1725 r,	
Selling Unit of Measure					
Service Factor				٢	
Shaft Diameter				1.	
Short Description			6 HP. 1800 RPM. Frame	Size 184T, Standard, 1 PH, 2	
Standards			,	N	
Starting of Motor				Direct or	
Stocked At					
(Warehouses)		China Alabama, United State: Alaska, United State:			
				1800 r,	
Type of Duty				Continu	
Voltage Rating				2	

36G510X288G1 3/3

Categories

 $Motors \ and \ Generators \rightarrow NEMA \ Low \ Voltage \ AC \ Motors \rightarrow General \ Purpose \ Motors \rightarrow Single \ Phase \ Open$



