



 PRODUCT-DETAILS

660998

No Description Available



General Information

| | |
|-------------------------|-----------------------------|
| Global Commercial Alias | 660998 |
| Product ID | 7B660998 |
| ABB Type Designation | RAPTOR 4HQD-JA HUB ALUMINUM |
| Catalog Description | No Description Available |

Additional Information

| | |
|--------------------|-------------------------|
| Coupling Type | Elastomeric |
| Coupling Style | Split-Tire |
| Coupling Size | 4 |
| Shaft Spacing | Close Coupled Spacer |
| Coupling Component | Hub |
| Shaft Attachment | Bushed |
| Bushing Type | QD |
| Bushing Size | JA |

Sealing and Lubrication

| | |
|-------------|------|
| Lubrication | None |
|-------------|------|

Technical

| | |
|---------------------------|----------------------------------|
| Rated Torque | 558 in·lb |
| Maximum Speed | 7500 r/min |
| Horsepower Per 100 Rating | 0.89 Hp |
| Angular Misalignment | 4 ° |
| Parallel Misalignment | 0.1875 in |
| Axial Misalignment | 0.3125 in |
| Temperature Rating | Maximum 220 °F Minimum -45 °F |

Dimensions

| | |
|-------------------|-------------------------------------|
| Bore Diameter | Maximum 1.1875 in Minimum 0.5 in |
| Bore Length | 0.88 in |
| Outside Diameter | 2.6 in |
| Product Net Width | 0 cm |

Classifications

| | |
|----------------------|-----------------------------|
| ABB Type Designation | RAPTOR 4HQD-JA HUB ALUMINUM |
|----------------------|-----------------------------|

Categories

Mechanical Power Transmission → Couplings → Elastomeric Couplings → Split-Tire (Raptor)

