
 PRODUCT-DETAILS

RL1324A

Fan and Blower 0.75 Hp 115 V (RL1324A)



General Information

Global Commercial Alias	RL1324A
Product ID	7BRL1324A
ABB Type Designation	.75HP,1725RPM,1PH,60HZ,56,3424L,OPE
Catalog Description	Fan and Blower 0.75 Hp 115 V (RL1324A)

Additional Information

ABB Type Designation	.75HP,1725RPM,1PH,60HZ,56,3424L,OPE
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6203, Ball
Bearing NDE	6203
Brake Present	No
Brand / Label	Baldor-Reliance
Catalog Number	RL1324A
Certification Agency	CSA UR
Country of Origin	United States (US)



Customs Tariff Number	85013100
Design	N
Dimension Diagram	34LYK018
Direction of Rotation	Both sides
Drive End Flange Type	Resilient Mount
ETIM 7	EC001851 - Electric motor
Efficiency Level	Not Regulated / Exempt
Electrical Data	

Current

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Enclosure Type	OPEN
Frame Material	Steel
Frame Size	56
Frequency (f)	60 Hz
Global Commercial Alias	RL1324A
Gross Volume	2110.969 in ³
Gross Weight	31 lb
Horsepower Rating UL/CSA	0.750 Hp
IC Class	OPEN
IDEA Granular Category Code (IGCC)	1318 >> Heating and cooling system motor AC
IE Class Data (50 Hz)	IE Class NA
IE Class Data (60 Hz)	IE Class NA
IM Class	F1
Insulation Class	B
Invoice Description	.75HP,1725RPM,1PH,60HZ,56,3424L,OPEN,F1
Lubrication	Regreasable
Made To Order	No
Medium Description	Fan and Blower, 0.75 HP, 1800 RPM, Frame Size 56, ResilientMount Mounting, 1 Phase, OPEN Enclosure, 115/230 V, 60 Hz (RL1324A)
Minimum Order Quantity	1 piece
Motor Base Type	Resilient
Motor Frame Size	56
Mounting Orientation	Horizontal
Mounting Position	F1
NEMA Design Code	N
Number of Phases	1
Number of Poles	4
Number of Poles (High)	4
Number of Speeds	Single Speed
Order Multiple	1 piece
Output Power	0.75 Hp
Power Factor	71 %
Product Name	Fan and Blower
Product Net Depth / Length	16.5 in
Product Net Height	11.125 in
Product Net Weight	31 lb
Product Net Width	11.5 in

Freq

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Power

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Speed

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Voltage

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":
The expression contains undefined function call GetListItemValue().

Product Type	Undefined
Quote Only	No
Rated Current (I _n)	10.8 A 5.4 A
Rated Efficiency	71 %
Rated Speed	1725 r/min
Selling Unit of Measure	piece
Service Factor	1.00
Service Factor Percentage	1.00 %
Shaft Diameter	0.63 in
Short Description	0.75 HP, 1800 RPM, Frame Size 56, ResilientMount, 1 PH, OPEN, 115/230 V
Standards	NEMA
Starting of Motor	Direct On Line
Stocked At (Warehouses)	China Alabama, United States Alaska, United States
Temperature Class Default	1800 r/min --
Two Speed Motor	No
Type of Duty	Continuous
UNSPSC	26101105
Voltage Code	G
Voltage Rating	115 V 230 V

Categories

Motors and Generators → NEMA Low Voltage AC Motors → HVAC Motors → Fan and Blower Motors



