

---

 PRODUCT-DETAILS

# VJPFPM2546T-2/4

## Pump Motor 60 Hp 200 V (VJPFPM2546T-2/4)




---

**General Information**

Global Commercial Alias	VJPFPM2546T-2/4
Product ID	7BVJPFPM2546T-2/4
ABB Type Designation	60HP,3520RPM,3PH,60HZ,326JP,4062M,O
Catalog Description	Pump Motor 60 Hp 200 V (VJPFPM2546T-2/4)

---

**Additional Information**

ABB Type Designation	60HP,3520RPM,3PH,60HZ,326JP,4062M,O
Ambient Temperature	40 °C
Bearing	6312, Ball
Bearing NDE	6309
Brake Present	No
Brand / Label	Baldor-Reliance
Catalog Number	VJPFPM2546T-2/4
Certification Agency	CSA EEV UL
Country of Origin	United States (US)
Customs Tariff Number	85015230









Dimension Diagram	40LYL037
Drive End Flange Type	C-Face
ETIM 7	EC001851 - Electric motor
Efficiency Level	Energy Efficiency (NEMA 12-11)
Electrical Data	

**Current**

An error has occurred while processing HtmlTextBox "":  
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":  
The expression contains undefined function call GetListItemValue().

Enclosure Type	OPSB
Frame Material	Steel
Frame Size	326
Frequency (f)	60 Hz
Global Commercial Alias	VJPFPM2546T-2/4
Gross Volume	24317.313 in <sup>3</sup>
Gross Weight	385 lb
IDEA Granular Category Code (IGCC)	1320 >> Pump motor AC
Insulation Class	F
Invoice Description	60HP,3520RPM,3PH,60HZ,326JP,4062M,OPSB,F
Made To Order	No
Medium Description	Fire Pump, 60 HP, Frame Size 326Jp, C-Face Mounting, 3 Phase, OPSB Enclosure, (VJPFPM2546T-2/4)
Minimum Order Quantity	1 piece
Motor Base Type	Footless
Motor Frame Size	326JP
Mounting Orientation	Horizontal
Mounting Position	F1
NEMA Design Code	B
Number of Phases	3
Number of Poles	2
Number of Poles (High)	2
Number of Speeds	Single Speed
Order Multiple	1 piece
Output Power	60 Hp
Power Factor	89 %
Product Name	Fire Pump
Product Net Depth / Length	43.25 in
Product Net Height	21.625 in
Product Net Weight	385 lb
Product Net Width	26 in
Product Type	Undefined
Quote Only	No
Rated Current (I <sub>n</sub> )	78 A
Rated Efficiency	93 %
Rated Speed	3520 r/min
Selling Unit of Measure	piece
Service Factor	1.15
Shaft Diameter	1.25 in
Short Description	60 HP, Frame Size 326Jp, C-Face, 3 PH, OPSB,
Standards	NEMA

---

**Freq**

An error has occurred while processing HtmlTextBox "":  
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":  
The expression contains undefined function call GetListItemValue().

---

---

**Power**

An error has occurred while processing HtmlTextBox "":  
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":  
The expression contains undefined function call GetListItemValue().

---



---

**Speed**

An error has occurred while processing HtmlTextBox "":  
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":  
The expression contains undefined function call GetListItemValue().

---

---

**Voltage**

An error has occurred while processing HtmlTextBox "":  
The expression contains undefined function call GetListItemValue().

An error has occurred while processing HtmlTextBox "":  
The expression contains undefined function call GetListItemValue().

---

Starting of Motor	Y-Start/Delta Run
Stocked At (Warehouses)	China Alabama, United States Alaska, United States
Type of Duty	3600 r/min Continuous
UNSPSC	26101107
Voltage Rating	200 V 400 V

---

## Categories

---

Motors and Generators → NEMA Low Voltage AC Motors → Pump Motors → Fire Pump Motors









