



PRODUCT-DETAILS

HTFX234065**8.3KV 65A FX FULL-RAGE FUSE, OUTDOO****General Information**

Extended Product Type	HTFX234065
Product ID	7TAA120700R0008
Catalog Description	8.3KV 65A FX FULL-RAGE FUSE, OUTDOO
Long Description	8.3kV 65 Amp FX stvle full range fuse

Ordering

UPC	783786807727
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 EA
Package Level 1 Width	76.2 mm 3 in
Package Level 1 Height	76.2 mm 3 in
Package Level 1 Depth /	406.4 mm

Length	16 in
Package Level 2 Units	8 EA
Package Level 2 Width	330.2 mm 13 in
Package Level 2 Height	279.4 mm 11 in
Package Level 2 Depth / Length	469.9 mm 18.5 in

Technical UL/CSA

Short-Circuit Current Rating (SCCR)	50,000 A
--	----------

Additional Information

Application	Installed in Drywall Canisters for Distribution Transformer Protection, Mounted with Spades, Externally mounted on Overhead distribution systems, Installed in Elastimold MCAN Rubber Molded Canister for Deadfront/Submersible applications, Installed directly in Oil.
Brand / Label	Hi-Tech
Current Rating	65 A
Effective Date	20090218
Material	Tin-Plated Brass Caps, Resin-Rich Filament Wound Glass/Epoxy Body. Painted
Mounting Type	Spade Mount
Product Name	In circuits of 2,300 V or more
Product Type	Full-Range Current-Limiting Fuse
Size	Diameter 2.2 in
Special Functions	Painted with Spades
Standards	ANSI/IEEE Standards.
Voltage Rating	8.3 kV

Certificates and Declarations

Data Sheet, Technical Information	HTFX234065
--------------------------------------	------------

Classifications

ETIM 7	EC003507 - Medium-/high voltage fuse
ETIM 8	EC003507 - Medium-/high voltage fuse
UNSPSC	39121626
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4980 >> Medium voltage fuse

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

