



 PRODUCT-DETAILS

J3-666-15-SV-L

15KV MULTI-POINT JUNCTION SERIES J



General Information

Extended Product Type	J3-666-15-SV-L
Product ID	7TAA122020R0327
Catalog Description	15KV MULTI-POINT JUNCTION SERIES J
Long Description	3 Point Junction, three - 600 Amp Bushing interface, 15KV, with Bracket, SV - Optional 6 -1/2 inch spacing. Left Parking Stand.

Ordering

UPC	75114371520
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 EA
Package Level 1 Width	25.4 mm 1 in
Package Level 1 Height	25.4 mm

	1 in
Package Level 1 Depth / Length	25.4 mm
	1 in

Additional Information

Application	Suited for Subsurface, Vault or Padmount Applications and can be used for Sectionalizing, Looping, Tapping and Equipment Bypass.
Brand / Label	Elastimold
Connection Type	Push-In
Effective Date	20180501
Material	EPDM Rubber and Stainless Steel Mounting Brackets.
Mounting Type	No Tilt Mounting Bracket.
Product Name	Terminals, electrical splices and electrical couplings
Product Type	Multi-Point Junction - 3 Points
Size	Overall Length 21.5 inches, Width 6.75 inches.
Special Functions	6-1/2 inch Center Spacing. Left Parking Stand.
Standards	ANSI/IEEE Standard 386
Temperature Range	-40 to +65 °C

Certificates and Declarations

Data Sheet, Technical Information	J3-666-15-SV-L
-----------------------------------	----------------

Classifications

UNSPSC	26121630
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	1779 >> Cable accessories

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

