




---

 PRODUCT-DETAILS

# K650S-LM0380-LM0380

## PERMANENT IN-LINE SPLICE



Product image  
not available

---

**General Information**

Extended Product Type	K650S-LM0380-LM0380
Product ID	7TAA123400R0022
Catalog Description	PERMANENT IN-LINE SPLICE
Long Description	15/25kV, Aluminum Permanent In-Line/Straight Splice, Cable Insulation Diameter LM - 1.280-1.430 inch, Conductor Size 380 is 750kcmil Stranded/Compressed. Includes EPDM Rubber 1-Piece Housing for Splice.

---

**Ordering**

UPC	783786400942
Country of Origin	United States (US)
Selling Unit of Measure	each

---

**Container Information**

Package Level 1 Units	1 EA
Package Level 1 Width	266.7 mm 10.5 in

Package Level 1 Height	111.252 mm 4.38 in
Package Level 1 Depth / Length	336.55 mm 13.25 in

### Additional Information

Application	15/25 kV
Brand / Label	Elastimold
Connection Type	Compression
Effective Date	20030605
Insulation Material	EPDM Rubber Housing
Material	Aluminum
Product Name	Terminals, electrical splices and electrical couplings
Product Type	Compression Splice

### Certificates and Declarations

Data Sheet, Technical Information	K650S-LM0380-LM0380
-----------------------------------	---------------------

### Classifications

ETIM 6	EC001060 - Crimp splices for aluminium conductor
ETIM 7	EC001060 - Crimp splices for aluminium conductor
ETIM 8	EC001060 - Crimp splices for aluminium conductor
UNSPSC	39121449
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4669 >> Wire or cable compression splice

### Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories



Product image  
not available