



PRODUCT-DETAILS

K650S-M0380-M0380

PERMANENT IN-LINE SPLICE



Product image
not available

General Information

Extended Product Type	K650S-M0380-M0380
Product ID	7TAA123400R0024
Catalog Description	PERMANENT IN-LINE SPLICE
Long Description	15/25kV, Aluminum Permanent In-Line/Straight Splice, Cable Insulation Diameter M - 1.370-1.630 inch, Conductor Size 380 is 750kcmil Stranded/Compressed. Includes EPDM Rubber 1-Piece Housing for Splice.

Ordering

UPC	783786654604
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 EA
Package Level 1 Width	266.7 mm 10.5 in

Package Level 1 Height	111.252 mm 4.38 in
Package Level 1 Depth / Length	336.55 mm 13.25 in

Additional Information

Application	15/25 kV
Brand / Label	Elastimold
Connection Type	Compression
Effective Date	19980115
Insulation Material	EPDM Rubber Housing
Material	Aluminum
Product Name	Terminals, electrical splices and electrical couplings
Product Type	Compression Splice

Certificates and Declarations

Data Sheet, Technical Information	K650S-M0380-M0380
-----------------------------------	-------------------

Classifications

ETIM 6	EC001060 - Crimp splices for aluminium conductor
ETIM 7	EC001060 - Crimp splices for aluminium conductor
ETIM 8	EC001060 - Crimp splices for aluminium conductor
UNSPSC	39121449
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4669 >> Wire or cable compression splice

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories



Product image
not available