K650S-N0380-N0380 1/3



PRODUCT-DETAILS

## K650S-N0380-N0380 PERMANENT IN-LINE SPLICE



General Information	
Extended Product Type	K650S-N0380-N0380
Product ID	7TAA123400R0025
EAN	5414363135364
Catalog Description	PERMANENT IN-LINE SPLICE
Long Description	15/25kV, Aluminum Permanent In-Line/Straight Splice, Cable Insulation Diameter N - 1.515-1.780 inch, Conductor Size 380 is 750kcmil Stranded/Compressed. Includes EPDM Rubber 1-Piece Housing for Splice.

Ordering	
EAN	5414363135364
UPC	783786485970
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 EA

K650S-N0380-N0380 2/3

Package Level 1 Width	266.7 mm
	10.5 in
Package Level 1 Height	111.252 mm
	4.38 in
Package Level 1 Depth /	336.55 mm
Length	13.25 in

Additional Information	
Application	15/25 kV
Brand / Label	Elastimold
Connection Type	Compression
Effective Date	20060512
Insulation Material	EPDM Rubber Housing
Material	Aluminum
Product Name	Terminals, electrical splices and electrical couplings
Product Type	Compression Splice

Certificates and Declarations	
Data Sheet, Technical	K650S-N0380-N0380
Information	

Classifications	
ETIM 6	EC001060 - Crimp splices for aluminium conductor
ETIM 7	EC001060 - Crimp splices for aluminium conductor
ETIM 8	EC001060 - Crimp splices for aluminium conductor
UNSPSC	39121449
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4669 >> Wire or cable compression splice

## **Categories**

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Cable\ Accessories\ and\ Apparatus \rightarrow Cable\ Accessories$ 

K650S-N0380-N0380 3/3

