



 PRODUCT-DETAILS

168FLR3-D0270

HOUSING FOR 8.3KV CLF



General Information

Extended Product Type	168FLR3-D0270
Product ID	7TAA124110R0048
EAN	5414363178668
Catalog Description	HOUSING FOR 8.3KV CLF
Long Description	Molded Current Limiting Fuse Housing, Nominal Fuse Voltage Rating 8.3kV, Fuse Test Port - Two Capacitive Test Ports, Large Housing, Cable Insulation Diameter 0.890 inch - 1.220 inch / 25-31mm, Aluminum Conductor size 4/0 AWG Stranded/Compressed.

Ordering

EAN	5414363178668
UPC	783786503285
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 EA
-----------------------	------

Package Level 1 Width	25.4 mm 1 in
Package Level 1 Height	25.4 mm 1 in
Package Level 1 Depth / Length	25.4 mm 1 in

Additional Information

Application	Protect Light Duty Underground Distribution Systems
Brand / Label	Elastimold
Color	Black
Current Rating	200 A
Effective Date	20060926
Insulation Material	Yes, EPDM Rubber
Material	EPDM Rubber
Product Name	In circuits of 2,300 V or more
Product Type	Loadbreak Fused Elbow Connector
Size	Length 21.12 inches from bottom to center of Bushing
Special Functions	Full-Range Current-Limiting Fusing with 50kA Interrupting Capability. Hotstick Operable 15kV Loadbreak Elbow Switching.
Standards	IEEE 386, ANSI C37.40, ANSI C37.41, ANSI C37.47
Temperature Range	-40 to +65 °C
Voltage Rating	8.3 kV

Certificates and Declarations

Data Sheet, Technical Information	168FLR3-D0270
-----------------------------------	---------------

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

