



 PRODUCT-DETAILS

274FLR3-B0250

FUSED ELBOW HOUSING 17.2KV



General Information

Extended Product Type	274FLR3-B0250
Product ID	7TAA124130R0008
Catalog Description	FUSED ELBOW HOUSING 17.2KV
Long Description	Molded Current Limiting Fuse Housing, Nominal Fuse Voltage Rating 17.2kV, Fuse Test Port - Two Capacitive Test Ports, Large Housing, Cable Insulation Diameter 0.635 inch - 0.905 inch / 16-23mm, Aluminum Conductor size 2/0 AWG Stranded Compressed, 3/0 AWG Solid Compact

Ordering

UPC	783786794966
Country of Origin	United States (US)
Selling Unit of Measure	each

Container Information

Package Level 1 Units	1 EA
Package Level 1 Width	120.65 mm

	4.75 in
Package Level 1 Height	400.05 mm
	15.75 in
Package Level 1 Depth / Length	368.3 mm
	14.5 in

Additional Information

Application	Protect Light Duty Underground Distribution Systems
Brand / Label	Elastimold
Color	Black
Current Rating	200 A
Effective Date	20081205
Includes	Elbow Connector Housing, Crimp Connector, Probe Lug, Tube of Lubricatn, Installation Instructions, Crimp Chart, V.D. Cap-Peroxide
Insulation Material	Yes, EPDM Rubber
Material	EPDM Rubber
Product Name	Terminals, electrical splices and electrical couplings
Product Type	Loadbreak Fused Elbow Connector with Test Point
Size	Length 21.12 inches from bottom to center of Bushing
Special Functions	Full-Range Current-Limiting Fusing with 50kA Interrupting Capability. Hotstick Operable 25/28kV Loadbreak Elbow Switching.
Standards	IEEE 386, ANSI C37.40, ANSI C37.41, ANSI C37.47
Temperature Range	-40 to +65 °C
Voltage Rating	15.5 to 16.2 kV

Certificates and Declarations

Data Sheet, Technical Information	274FLR3-B0250
-----------------------------------	---------------

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

